

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P206105

Luminaire Tested: **LD4B10D010 EU4B10209730 4LBSMW1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P206105
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LD4B10D010 EU4B10209730 4LBSMW1
Description: PORTFOLIO 4 INCH SHALLOW RECESSED DOWNLIGHT
SHALLOW DISTRIBUTION WITH MATTE WHITE TRIM
WATTAGE D010TR-10.05W DE010-10.58W D5LT-10.2W DMX-10.6W DL2-11.8W
DL3-11.1W DLE-11.39W
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 820.7 lumens
Efficiency: N/A
Efficacy: 82.9 lumens/watt
Spacing Criteria (0/90/45): 1.24 / 1.24 / 1.34
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 9.9
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P206105

CATALOG NUMBER: LD4B10D010 EU4B10209730 4LBSMW1

Luminous Intensity Polar Plot





TEST NUMBER: P206105

CATALOG NUMBER: LD4B10D010 EU4B10209730 4LBSMW1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				20	
RC	80				70				50				30				10				0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0	
RCR																						
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100				100
1	110	106	102	99	107	104	100	97	99	97	94	96	93	91	92	90	88	86				86
2	101	93	87	82	98	92	86	81	88	83	79	85	81	77	82	79	76	74				74
3	93	83	75	69	90	81	74	69	78	72	67	76	70	66	73	69	65	63				63
4	85	74	66	59	83	72	65	59	70	63	58	68	62	57	66	61	56	54				54
5	78	66	58	51	76	65	57	51	63	56	51	61	55	50	59	54	49	47				47
6	73	60	51	45	71	59	51	45	57	50	44	55	49	44	54	48	44	42				42
7	67	54	46	40	66	54	46	40	52	45	40	51	44	39	49	43	39	37				37
8	63	50	41	36	61	49	41	36	48	41	35	46	40	35	45	39	35	33				33
9	59	46	38	32	57	45	37	32	44	37	32	43	36	32	42	36	32	30				30
10	55	42	34	29	54	42	34	29	41	34	29	40	33	29	39	33	29	27				27

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P206105

CATALOG NUMBER: LD4B10D010 EU4B10209730 4LBSMW1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	31.3	3.8
10°-20°	89.3	10.9
20°-30°	134.5	16.4
30°-40°	160.1	19.5
40°-50°	159.7	19.5
50°-60°	129.9	15.8
60°-70°	79.9	9.7
70°-80°	31.0	3.8
80°-90°	5.0	0.6
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	255.1	31.1
0°-40°	415.2	50.6
0°-60°	704.9	85.9
0°-90°	820.7	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	820.7	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	331	
5°	330	31
15°	317	89
25°	293	135
35°	256	160
45°	208	160
55°	145	130
65°	80	80
75°	28	31
85°	4	5
90°	0	



TEST NUMBER: P206105

CATALOG NUMBER: LD4B10D010 EU4B10209730 4LBSMW1

CANDELA DISTRIBUTION (FULL):

	0°
0°	330.7
2.5°	331.1
5°	329.7
7.5°	327.7
10°	325.3
12.5°	320.9
15°	317.0
17.5°	311.2
20°	304.9
22.5°	299.1
25°	292.7
27.5°	284.0
30°	275.2
32.5°	267.0
35°	256.3
37.5°	244.6
40°	233.9
42.5°	220.8
45°	207.6
47.5°	193.5
50°	178.5
52.5°	162.9
55°	145.4
57.5°	128.4
60°	111.8
62.5°	95.8
65°	80.2
67.5°	65.6
70°	52.0
72.5°	39.4
75°	28.2
77.5°	18.5
80°	11.2
82.5°	6.8
85°	3.9
87.5°	1.9
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)