

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P206551

Luminaire Tested: **LD4B30D010 EU4B30509024 4LBCSMMS1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P206551
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LD4B30D010 EU4B30509024 4LBCSMMS1
Description: PORTFOLIO 4 INCH SHALLOW RECESSED DOWNLIGHT
SHALLOW DISTRIBUTION WITH CAST MATTE BLACK TRIM
WATTAGE D010TR-27.4W DE010-27.95W D5LT-27.65W DMX-27.73W DL2-29.56W
DL3-29.67W DLE-29.73W
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1859.2 lumens
Efficiency: N/A
Efficacy: 66.4 lumens/watt
Spacing Criteria (0/90/45): 1.16 / 1.16 / 1.27
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 28
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P206551

CATALOG NUMBER: LD4B30D010 EU4B30509024 4LBCSMMS1

Luminous Intensity Polar Plot





TEST NUMBER: P206551

CATALOG NUMBER: LD4B30D010 EU4B30509024 4LBCSMMS1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			100
1	111	107	103	100	108	105	101	98	100	98	95	97	94	92	93	91	90	88			88
2	102	95	89	84	99	93	88	83	90	85	81	86	83	79	83	80	78	76			76
3	94	85	77	72	92	83	76	71	80	74	70	77	73	69	75	71	67	65			65
4	87	76	68	62	84	74	67	61	72	66	61	70	64	60	68	63	59	57			57
5	80	68	60	54	78	67	59	54	65	58	53	63	57	53	61	56	52	50			50
6	74	62	54	48	72	61	53	47	59	52	47	58	51	47	56	51	46	44			44
7	69	56	48	42	67	56	48	42	54	47	42	53	46	42	51	46	41	40			40
8	64	52	44	38	63	51	43	38	50	43	38	48	42	38	47	42	37	36			36
9	60	48	40	35	59	47	40	34	46	39	34	45	39	34	44	38	34	32			32
10	57	44	36	31	55	43	36	31	43	36	31	42	35	31	41	35	31	29			29

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P206551

CATALOG NUMBER: LD4B30D010 EU4B30509024 4LBCSMMS1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	80.5	4.3
10°-20°	225.8	12.1
20°-30°	329.7	17.7
30°-40°	377.2	20.3
40°-50°	362.5	19.5
50°-60°	279.9	15.1
60°-70°	156.2	8.4
70°-80°	45.4	2.4
80°-90°	2.0	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	636.0	34.2
0°-40°	1013.1	54.5
0°-60°	1655.5	89.0
0°-90°	1859.2	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1859.2	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	854	
5°	847	80
15°	801	226
25°	717	330
35°	604	377
45°	473	362
55°	314	280
65°	156	156
75°	40	45
85°	1	2
90°	0	



TEST NUMBER: P206551

CATALOG NUMBER: LD4B30D010 EU4B30509024 4LBCSMMS1

CANDELA DISTRIBUTION (FULL):

	0°
0°	853.8
2.5°	853.8
5°	846.6
7.5°	843.0
10°	830.9
12.5°	816.5
15°	800.9
17.5°	785.2
20°	762.4
22.5°	744.3
25°	716.7
27.5°	689.0
30°	661.4
32.5°	633.7
35°	603.7
37.5°	573.6
40°	538.7
42.5°	507.5
45°	472.6
47.5°	432.9
50°	395.6
52.5°	354.7
55°	313.9
57.5°	271.8
60°	232.1
62.5°	192.4
65°	156.3
67.5°	122.7
70°	91.4
72.5°	63.7
75°	39.7
77.5°	20.4
80°	7.2
82.5°	2.4
85°	1.2
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)