

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P205935

Luminaire Tested: **LD4B30D010 EU4B30509727 4LBSGPH1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P205935
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LD4B30D010 EU4B30509727 4LBSGPH1
Description: PORTFOLIO 4 INCH SHALLOW RECESSED DOWNLIGHT
SHALLOW DISTRIBUTION WITH GRAPHITE HAZE TRIM
WATTAGE D010TR-27.4W DE010-27.95W D5LT-27.65W DMX-27.73W DL2-29.56W
DL3-29.67W DLE-29.73W
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 2630.3 lumens
Efficiency: N/A
Efficacy: 93.9 lumens/watt
Spacing Criteria (0/90/45): 1.16 / 1.16 / 1.26
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 28
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P205935

CATALOG NUMBER: LD4B30D010 EU4B30509727 4LBSGPH1

Luminous Intensity Polar Plot





TEST NUMBER: P205935

CATALOG NUMBER: LD4B30D010 EU4B30509727 4LBSGPH1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				20	
RC	80				70				50				30				10				0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0	
RCR																						
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100				100
1	111	107	103	100	108	105	102	99	101	98	96	97	95	93	93	91	90	88				88
2	102	95	89	84	100	93	88	83	90	85	82	87	83	80	84	81	78	76				76
3	94	85	78	72	92	83	77	71	80	75	70	78	73	69	75	71	68	66				66
4	87	76	68	62	85	75	67	62	72	66	61	70	65	60	68	63	59	57				57
5	80	68	60	54	78	67	60	54	65	59	53	63	58	53	62	56	52	50				50
6	74	62	54	48	73	61	53	48	59	52	47	58	52	47	56	51	47	45				45
7	69	57	48	43	68	56	48	43	54	47	42	53	47	42	52	46	42	40				40
8	65	52	44	38	63	51	44	38	50	43	38	49	42	38	48	42	38	36				36
9	60	48	40	35	59	47	40	35	46	39	35	45	39	34	44	38	34	32				32
10	57	44	37	32	56	44	36	32	43	36	31	42	36	31	41	35	31	30				30

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P205935

CATALOG NUMBER: LD4B30D010 EU4B30509727 4LBSGPH1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	115.0	4.4
10°-20°	322.9	12.3
20°-30°	470.9	17.9
30°-40°	537.0	20.4
40°-50°	515.1	19.6
50°-60°	394.5	15.0
60°-70°	216.5	8.2
70°-80°	57.6	2.2
80°-90°	0.9	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	908.8	34.6
0°-40°	1445.8	55.0
0°-60°	2355.4	89.5
0°-90°	2630.3	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2630.3	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1222	
5°	1212	115
15°	1146	323
25°	1023	471
35°	859	537
45°	669	515
55°	442	394
65°	218	216
75°	50	58
85°	0	1
90°	0	



TEST NUMBER: P205935

CATALOG NUMBER: LD4B30D010 EU4B30509727 4LBSGPH1

CANDELA DISTRIBUTION (FULL):

	0°
0°	1221.7
2.5°	1218.5
5°	1212.2
7.5°	1202.7
10°	1190.1
12.5°	1168.0
15°	1145.9
17.5°	1120.6
20°	1092.2
22.5°	1057.5
25°	1022.8
27.5°	988.1
30°	943.9
32.5°	902.8
35°	858.6
37.5°	814.4
40°	770.2
42.5°	722.9
45°	669.2
47.5°	615.6
50°	558.7
52.5°	498.8
55°	441.9
57.5°	385.1
60°	325.1
62.5°	268.3
65°	217.8
67.5°	167.3
70°	123.1
72.5°	82.1
75°	50.5
77.5°	22.1
80°	6.3
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)