

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P206764

Luminaire Tested: **LD4B30D010 EU4B30509730 4LBWWH1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P206764
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LD4B30D010 EU4B30509730 4LBWWH1
Description: PORTFOLIO 4 INCH 60 DEGREE CUTOFF RECESSED DOWNLIGHT
WIDE DISTRIBUTION WITH WHEAT TRIM
WATTAGE D010TR-27.4W DE010-27.95W D5LT-27.65W DMX-27.73W DL2-29.56W
DL3-29.67W DLE-29.73W
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1890.2 lumens
Efficiency: N/A
Efficacy: 67.5 lumens/watt
Spacing Criteria (0/90/45): 1.26 / 1.26 / 1.16
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 28
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P206764

CATALOG NUMBER: LD4B30D010 EU4B30509730 4LBWWH1

Luminous Intensity Polar Plot





TEST NUMBER: P206764

CATALOG NUMBER: LD4B30D010 EU4B30509730 4LBWWH1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100	100	100	100
1	113	110	107	104	110	107	105	103	103	101	100	100	98	97	96	95	94	92	92	92	92
2	106	101	96	92	104	99	95	91	96	92	89	93	90	87	90	87	85	84	84	84	84
3	100	93	87	82	98	91	86	82	88	84	80	86	82	79	84	80	78	76	76	76	76
4	94	85	79	74	92	84	78	74	82	77	73	80	75	72	78	74	71	69	69	69	69
5	88	79	72	67	86	78	71	67	76	70	66	74	69	65	72	68	65	63	63	63	63
6	83	73	66	61	81	72	65	61	70	64	60	69	64	60	67	63	59	58	58	58	58
7	78	67	60	56	76	67	60	55	65	59	55	64	59	55	63	58	54	53	53	53	53
8	73	62	56	51	72	62	55	51	61	55	51	60	54	50	59	54	50	49	49	49	49
9	69	58	51	47	68	58	51	47	57	51	47	56	50	47	55	50	46	45	45	45	45
10	65	54	48	43	64	54	48	43	53	47	43	52	47	43	51	46	43	41	41	41	41

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P206764

CATALOG NUMBER: LD4B30D010 EU4B30509730 4LBWWH1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	114.5	6.1
10°-20°	354.2	18.7
20°-30°	544.9	28.8
30°-40°	525.8	27.8
40°-50°	274.1	14.5
50°-60°	57.7	3.1
60°-70°	13.4	0.7
70°-80°	5.2	0.3
80°-90°	0.3	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1013.7	53.6
0°-40°	1539.4	81.4
0°-60°	1871.3	99.0
0°-90°	1890.2	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1890.2	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1182	
5°	1192	115
15°	1254	354
25°	1194	545
35°	853	526
45°	349	274
55°	52	58
65°	12	13
75°	5	5
85°	0	0
90°	0	



TEST NUMBER: P206764

CATALOG NUMBER: LD4B30D010 EU4B30509730 4LBWWH1

CANDELA DISTRIBUTION (FULL):

	0°
0°	1181.8
2.5°	1184.3
5°	1191.7
7.5°	1201.6
10°	1216.5
12.5°	1236.2
15°	1253.5
17.5°	1263.4
20°	1256.0
22.5°	1241.2
25°	1194.2
27.5°	1137.3
30°	1063.2
32.5°	964.3
35°	853.0
37.5°	731.9
40°	605.8
42.5°	479.7
45°	348.6
47.5°	234.9
50°	150.8
52.5°	91.5
55°	51.9
57.5°	32.1
60°	22.3
62.5°	17.3
65°	12.4
67.5°	9.9
70°	7.4
72.5°	7.4
75°	4.9
77.5°	2.5
80°	2.5
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)