

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P206036

Luminaire Tested: **LD4B30D010 EU4B30509035 4LBSB1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P206036
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LD4B30D010 EU4B30509035 4LBSB1
Description: PORTFOLIO 4 INCH SHALLOW RECESSED DOWNLIGHT
SHALLOW DISTRIBUTION WITH SPECULAR BLACK TRIM
WATTAGE D010TR-27.4W DE010-27.95W D5LT-27.65W DMX-27.73W DL2-29.56W
DL3-29.67W DLE-29.73W
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 2182.2 lumens
Efficiency: N/A
Efficacy: 77.9 lumens/watt
Spacing Criteria (0/90/45): 1.2 / 1.2 / 1.3
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 28
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P206036

CATALOG NUMBER: LD4B30D010 EU4B30509035 4LBSB1

Luminous Intensity Polar Plot





TEST NUMBER: P206036

CATALOG NUMBER: LD4B30D010 EU4B30509035 4LBSB1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				20	
RC	80				70				50				30				10				0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0	
RCR																						
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100				100
1	111	107	103	100	108	105	101	98	100	98	95	97	94	93	93	91	90	88				88
2	102	95	89	84	100	93	88	83	90	85	81	86	83	79	84	80	78	76				76
3	94	84	77	72	91	83	76	71	80	74	70	77	73	68	75	71	67	65				65
4	86	76	68	62	84	74	67	61	72	65	60	70	64	60	68	63	59	57				57
5	80	68	60	54	78	67	59	53	65	58	53	63	57	52	61	56	52	50				50
6	74	62	53	47	72	61	53	47	59	52	47	57	51	46	56	50	46	44				44
7	69	56	48	42	67	55	48	42	54	47	42	52	46	41	51	45	41	39				39
8	64	51	43	38	63	51	43	38	49	42	37	48	42	37	47	41	37	35				35
9	60	47	39	34	59	47	39	34	46	39	34	45	38	34	44	38	34	32				32
10	56	44	36	31	55	43	36	31	42	36	31	41	35	31	40	35	31	29				29

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P206036

CATALOG NUMBER: LD4B30D010 EU4B30509035 4LBSB1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	90.9	4.2
10°-20°	257.8	11.8
20°-30°	383.5	17.6
30°-40°	446.3	20.4
40°-50°	435.0	19.9
50°-60°	334.6	15.3
60°-70°	184.9	8.5
70°-80°	49.0	2.2
80°-90°	0.4	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	732.1	33.6
0°-40°	1178.4	54.0
0°-60°	1947.9	89.3
0°-90°	2182.2	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2182.2	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	963	
5°	957	91
15°	913	258
25°	833	383
35°	716	446
45°	564	435
55°	373	335
65°	185	185
75°	42	49
85°	0	0
90°	0	



TEST NUMBER: P206036

CATALOG NUMBER: LD4B30D010 EU4B30509035 4LBSB1

CANDELA DISTRIBUTION (FULL):

0°	
0°	962.7
2.5°	962.7
5°	957.1
7.5°	948.8
10°	943.3
12.5°	926.7
15°	912.9
17.5°	899.0
20°	879.7
22.5°	860.3
25°	832.6
27.5°	805.0
30°	777.3
32.5°	746.9
35°	716.5
37.5°	677.7
40°	644.5
42.5°	608.6
45°	564.3
47.5°	522.8
50°	475.8
52.5°	426.0
55°	373.4
57.5°	323.7
60°	276.6
62.5°	229.6
65°	185.3
67.5°	143.8
70°	105.1
72.5°	71.9
75°	41.5
77.5°	19.4
80°	2.8
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)