

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P208407

Luminaire Tested: **LD4B40D010 EU4B30508027 4LBSLI1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P208407
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LD4B40D010 EU4B30508027 4LBSLI1
Description: PORTFOLIO 4 INCH SHALLOW RECESSED DOWNLIGHT
SHALLOW DISTRIBUTION WITH SPECULAR CLEAR TRIM
WATTAGE D010TR-43.02W DE010-42.54W D5LT-42.539W DMX-41.87W DL2-41.57W
DL3-44.71W DLE-39.33W
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 4004.7 lumens
Efficiency: N/A
Efficacy: 95.8 lumens/watt
Spacing Criteria (0/90/45): 0.91 / 0.91 / 1
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 41.8
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P208407

CATALOG NUMBER: LD4B40D010 EU4B30508027 4LBSLI1

Luminous Intensity Polar Plot





TEST NUMBER: P208407

CATALOG NUMBER: LD4B40D010 EU4B30508027 4LBSLI1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10		0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100		
1	112	108	105	102	109	106	103	101	102	100	98	98	96	95	95	93	92	90		
2	104	98	93	88	102	96	91	87	93	89	85	90	86	84	87	84	82	80		
3	97	89	82	77	95	87	81	77	84	79	75	82	78	74	79	76	73	71		
4	90	81	73	68	88	79	73	68	77	71	67	75	70	66	73	69	65	63		
5	84	73	66	61	82	72	65	60	70	64	60	69	63	59	67	62	59	57		
6	79	67	60	54	77	66	59	54	65	58	54	63	58	53	62	57	53	51		
7	74	62	54	49	72	61	54	49	60	53	49	58	53	48	57	52	48	46		
8	69	57	50	45	68	57	50	45	55	49	45	54	49	44	53	48	44	42		
9	65	53	46	41	64	53	46	41	52	45	41	51	45	41	50	44	41	39		
10	61	50	43	38	60	49	42	38	48	42	38	47	42	38	46	41	37	36		

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P208407

CATALOG NUMBER: LD4B40D010 EU4B30508027 4LBSLI1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	259.3	6.5
10°-20°	661.3	16.5
20°-30°	856.9	21.4
30°-40°	839.6	21.0
40°-50°	711.6	17.8
50°-60°	466.5	11.6
60°-70°	187.5	4.7
70°-80°	21.4	0.5
80°-90°	0.6	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1777.4	44.4
0°-40°	2617.0	65.3
0°-60°	3795.2	94.8
0°-90°	4004.7	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	4004.7	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2860	
5°	2784	259
15°	2358	661
25°	1871	857
35°	1334	840
45°	927	712
55°	519	467
65°	182	188
75°	9	21
85°	0	1
90°	0	



TEST NUMBER: P208407

CATALOG NUMBER: LD4B40D010 EU4B30508027 4LBSL11

CANDELA DISTRIBUTION (FULL):

	0°
0°	2859.5
2.5°	2837.3
5°	2784.1
7.5°	2695.4
10°	2584.6
12.5°	2464.9
15°	2358.5
17.5°	2243.3
20°	2128.0
22.5°	2003.9
25°	1870.9
27.5°	1733.4
30°	1591.6
32.5°	1458.6
35°	1334.4
37.5°	1232.5
40°	1121.6
42.5°	1024.1
45°	926.6
47.5°	824.6
50°	722.6
52.5°	620.7
55°	518.7
57.5°	425.6
60°	336.9
62.5°	257.1
65°	181.8
67.5°	119.7
70°	70.9
72.5°	31.0
75°	8.9
77.5°	4.4
80°	4.4
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)