

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P207796

Luminaire Tested: **LD4B40D010 EU4B30508030 4LBNGPH1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P207796
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LD4B40D010 EU4B30508030 4LBNGPH1
Description: PORTFOLIO 4 INCH 50 DEGREE CUTOFF RECESSED DOWNLIGHT
NARROW DISTRIBUTION WITH GRAPHITE HAZE TRIM
WATTAGE D010TR-43.02W DE010-42.54W D5LT-42.539W DMX-41.87W DL2-41.57W
DL3-44.71W DLE-39.33W
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1914.7 lumens
Efficiency: N/A
Efficacy: 45.8 lumens/watt
Spacing Criteria (0/90/45): 0.86 / 0.86 / 0.88
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 41.8
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P207796

CATALOG NUMBER: LD4B40D010 EU4B30508030 4LBNGPH1

Luminous Intensity Polar Plot





TEST NUMBER: P207796

CATALOG NUMBER: LD4B40D010 EU4B30508030 4LBNGPH1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	114	111	108	106	111	109	106	104	105	103	101	101	100	98	97	96	95	94			
2	108	103	99	96	106	101	98	95	98	95	93	95	93	91	93	91	89	87			
3	103	96	91	87	101	95	90	87	92	88	85	90	87	84	88	85	83	81			
4	97	90	84	80	96	89	84	80	87	82	79	85	81	78	83	80	77	76			
5	93	84	78	74	91	83	78	74	82	77	73	80	76	73	78	75	72	70			
6	88	79	73	69	86	78	73	69	77	72	68	75	71	68	74	70	67	66			
7	84	74	68	64	82	74	68	64	72	67	64	71	67	63	70	66	63	62			
8	80	70	64	60	78	70	64	60	68	63	60	67	63	59	66	62	59	58			
9	76	66	60	56	75	66	60	56	65	60	56	64	59	56	63	59	56	54			
10	72	63	57	53	71	62	57	53	61	56	53	61	56	53	60	56	52	51			

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P207796

CATALOG NUMBER: LD4B40D010 EU4B30508030 4LBNGPH1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	208.8	10.9
10°-20°	523.3	27.3
20°-30°	637.8	33.3
30°-40°	420.8	22.0
40°-50°	96.9	5.1
50°-60°	18.5	1.0
60°-70°	6.8	0.4
70°-80°	1.8	0.1
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1369.9	71.5
0°-40°	1790.7	93.5
0°-60°	1906.1	99.5
0°-90°	1914.7	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1914.7	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2296	
5°	2240	209
15°	1874	523
25°	1401	638
35°	673	421
45°	107	97
55°	19	19
65°	5	7
75°	0	2
85°	0	0
90°	0	



TEST NUMBER: P207796

CATALOG NUMBER: LD4B40D010 EU4B30508030 4LBNGPH1

CANDELA DISTRIBUTION (FULL):

	0°
0°	2296.2
2.5°	2291.5
5°	2240.5
7.5°	2170.9
10°	2078.2
12.5°	1985.4
15°	1874.0
17.5°	1758.1
20°	1637.5
22.5°	1530.8
25°	1400.9
27.5°	1271.0
30°	1104.0
32.5°	899.9
35°	672.6
37.5°	468.5
40°	301.5
42.5°	185.5
45°	106.7
47.5°	55.7
50°	32.5
52.5°	27.8
55°	18.6
57.5°	13.9
60°	13.9
62.5°	9.3
65°	4.6
67.5°	4.6
70°	4.6
72.5°	4.6
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)