

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P207601

Luminaire Tested: **LD4B40D010 EU4B30509730 4LBMMW1**

Issue Date: 3/3/2020

**Test Information**

Test Method: LM-41-14  
Report Number: P207601  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)  
Test Lab: INNOVATION CENTER-P3  
Issue Date: 3/3/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: io LED  
Catalog Number: LD4B40D010 EU4B30509730 4LBMMW1  
Description: PORTFOLIO 4 INCH 50 DEGREE CUTOFF RECESSED DOWNLIGHT  
MEDIUM DISTRIBUTION WITH MATTE WHITE TRIM  
WATTAGE D010TR-43.02W DE010-42.54W D5LT-42.539W DMX-41.87W DL2-41.57W  
DL3-44.71W DLE-39.33W  
Light Source: HIGH LUMEN LED  
Ballast/Driver: ELECTRONIC DRIVER

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 2388.0 lumens  
Efficiency: N/A  
Efficacy: 57.1 lumens/watt  
Spacing Criteria (0/90/45): 0.99 / 0.99 / 0.97  
Luminous Opening: Point Source (0' x 0' x 0')  
CIE Type: Direct


Input Watts (W): 41.8  
Input Voltage (V): NR  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P207601

CATALOG NUMBER: LD4B40D010 EU4B30509730 4LBMMW1

### Luminous Intensity Polar Plot





TEST NUMBER: P207601

CATALOG NUMBER: LD4B40D010 EU4B30509730 4LBMMW1

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	112	108	105	102	109	106	103	100	102	99	97	98	96	94	94	93	91	89			
2	104	98	92	88	102	96	91	87	93	89	85	89	86	83	87	84	81	80			
3	97	89	83	77	95	87	82	77	85	80	76	82	78	74	80	76	73	71			
4	91	81	74	69	89	80	74	69	78	72	68	76	71	67	74	69	66	64			
5	85	75	67	62	83	74	67	62	72	66	61	70	65	61	68	64	60	58			
6	80	69	62	56	78	68	61	56	66	60	56	65	59	55	63	59	55	53			
7	75	64	57	52	74	63	56	51	62	56	51	60	55	51	59	54	50	49			
8	71	59	52	47	69	59	52	47	58	51	47	56	51	47	55	50	47	45			
9	67	55	48	44	66	55	48	44	54	48	44	53	47	43	52	47	43	42			
10	63	52	45	41	62	51	45	41	51	45	40	50	44	40	49	44	40	39			

**AVERAGE LUMINANCE (cd/sqm):**





TEST NUMBER: P207601

CATALOG NUMBER: LD4B40D010 EU4B30509730 4LBMMW1

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	168.0	7.0
10°-20°	450.5	18.9
20°-30°	599.0	25.1
30°-40°	489.9	20.5
40°-50°	285.3	11.9
50°-60°	189.2	7.9
60°-70°	124.4	5.2
70°-80°	65.7	2.7
80°-90°	16.0	0.7
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1217.5	51.0
0°-40°	1707.4	71.5
0°-60°	2181.9	91.4
0°-90°	2388.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2388.0	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	1813	
5°	1792	168
15°	1605	450
25°	1315	599
35°	782	490
45°	360	285
55°	211	189
65°	124	124
75°	62	66
85°	14	16
90°	0	



TEST NUMBER: P207601

CATALOG NUMBER: LD4B40D010 EU4B30509730 4LBMMW1

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	1812.8
2.5°	1809.4
5°	1792.1
7.5°	1750.6
10°	1705.6
12.5°	1664.1
15°	1605.2
17.5°	1539.5
20°	1484.2
22.5°	1408.1
25°	1314.6
27.5°	1214.3
30°	1086.3
32.5°	934.1
35°	781.9
37.5°	643.5
40°	522.4
42.5°	429.0
45°	359.8
47.5°	304.4
50°	266.4
52.5°	235.3
55°	211.0
57.5°	186.8
60°	162.6
62.5°	145.3
65°	124.5
67.5°	107.2
70°	89.9
72.5°	76.1
75°	62.3
77.5°	48.4
80°	34.6
82.5°	24.2
85°	13.8
87.5°	3.5
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093







— 0°-180°







(END OF REPORT)