

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P207180

Luminaire Tested: **LD4B40D010 EU4B30508040 4LBMH1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P207180
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LD4B40D010 EU4B30508040 4LBMH1
Description: PORTFOLIO 4 INCH 50 DEGREE CUTOFF RECESSED DOWNLIGHT
MEDIUM DISTRIBUTION WITH SEMI-SPECULAR CLEAR TRIM
WATTAGE D010TR-43.02W DE010-42.54W D5LT-42.539W DMX-41.87W DL2-41.57W
DL3-44.71W DLE-39.33W
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 3183.9 lumens
Efficiency: N/A
Efficacy: 76.2 lumens/watt
Spacing Criteria (0/90/45): 0.95 / 0.95 / 0.93
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 41.8
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P207180

CATALOG NUMBER: LD4B40D010 EU4B30508040 4LBMH1

Luminous Intensity Polar Plot





TEST NUMBER: P207180

CATALOG NUMBER: LD4B40D010 EU4B30508040 4LBMH1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	113	110	108	105	111	108	106	104	104	102	100	100	99	97	97	96	95	93			
2	107	102	98	94	105	100	96	93	97	94	91	94	91	89	91	89	87	85			
3	101	94	89	85	99	93	88	84	90	86	83	88	84	82	86	83	80	79			
4	96	88	82	77	94	86	81	77	84	80	76	82	78	75	80	77	74	73			
5	90	82	75	71	89	81	75	70	79	74	70	77	73	69	75	72	69	67			
6	86	76	70	65	84	75	69	65	74	68	64	72	68	64	71	67	64	62			
7	81	71	65	60	80	70	64	60	69	64	60	68	63	59	67	62	59	58			
8	77	67	60	56	75	66	60	56	65	59	56	64	59	55	63	58	55	54			
9	73	63	56	52	72	62	56	52	61	56	52	60	55	52	59	55	52	50			
10	69	59	53	49	68	59	53	49	58	52	49	57	52	48	56	52	48	47			

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P207180

CATALOG NUMBER: LD4B40D010 EU4B30508040 4LBMH1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	290.5	9.1
10°-20°	762.1	23.9
20°-30°	979.5	30.8
30°-40°	736.9	23.1
40°-50°	296.0	9.3
50°-60°	84.1	2.6
60°-70°	26.6	0.8
70°-80°	7.6	0.2
80°-90°	0.7	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2032.1	63.8
0°-40°	2769.0	87.0
0°-60°	3149.1	98.9
0°-90°	3183.9	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	3183.9	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	3157	
5°	3100	291
15°	2720	762
25°	2162	979
35°	1182	737
45°	365	296
55°	86	84
65°	24	27
75°	5	8
85°	0	1
90°	0	



TEST NUMBER: P207180

CATALOG NUMBER: LD4B40D010 EU4B30508040 4LBMH1

CANDELA DISTRIBUTION (FULL):

	0°
0°	3157.2
2.5°	3137.9
5°	3099.5
7.5°	3027.4
10°	2936.1
12.5°	2825.6
15°	2719.9
17.5°	2599.7
20°	2470.0
22.5°	2330.6
25°	2162.4
27.5°	1960.6
30°	1725.1
32.5°	1460.8
35°	1182.1
37.5°	922.6
40°	692.0
42.5°	509.4
45°	365.2
47.5°	249.9
50°	173.0
52.5°	120.1
55°	86.5
57.5°	62.5
60°	48.1
62.5°	33.6
65°	24.0
67.5°	19.2
70°	14.4
72.5°	9.6
75°	4.8
77.5°	4.8
80°	4.8
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)