

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P207813

Luminaire Tested: **LD4B50D010TE EU4B30509024 4LBNGPH1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P207813
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LD4B50D010TE EU4B30509024 4LBNGPH1
Description: PORTFOLIO 4 INCH 50 DEGREE CUTOFF RECESSED DOWNLIGHT
NARROW DISTRIBUTION WITH GRAPHITE HAZE TRIM
SINGLE DRIVER D010TE
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1760.0 lumens
Efficiency: N/A
Efficacy: 29.9 lumens/watt
Spacing Criteria (0/90/45): 0.86 / 0.86 / 0.88
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 58.77
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P207813

CATALOG NUMBER: LD4B50D010TE EU4B30509024 4LBNGPH1

Luminous Intensity Polar Plot





TEST NUMBER: P207813

CATALOG NUMBER: LD4B50D010TE EU4B30509024 4LBNGPH1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10		0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100		
1	114	111	108	106	111	109	106	104	105	103	101	101	100	98	97	96	95	94		
2	108	103	99	96	106	101	98	95	98	95	93	95	93	91	92	91	89	87		
3	103	96	91	87	101	95	90	87	92	88	85	90	87	84	88	85	83	81		
4	97	90	84	80	96	89	84	80	87	82	79	85	81	78	83	80	77	76		
5	93	84	78	74	91	83	78	74	82	77	73	80	76	73	78	75	72	70		
6	88	79	73	69	86	78	73	69	77	72	68	75	71	68	74	70	67	66		
7	84	74	68	64	82	74	68	64	72	67	64	71	67	63	70	66	63	62		
8	80	70	64	60	78	70	64	60	68	63	60	67	63	59	66	62	59	58		
9	76	66	60	56	75	66	60	56	65	60	56	64	59	56	63	59	56	54		
10	72	63	57	53	71	62	57	53	61	56	53	61	56	53	60	56	52	51		

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P207813

CATALOG NUMBER: LD4B50D010TE EU4B30509024 4LBNGPH1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	191.9	10.9
10°-20°	481.0	27.3
20°-30°	586.2	33.3
30°-40°	386.8	22.0
40°-50°	89.0	5.1
50°-60°	17.0	1.0
60°-70°	6.3	0.4
70°-80°	1.7	0.1
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1259.1	71.5
0°-40°	1645.9	93.5
0°-60°	1752.0	99.5
0°-90°	1760.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1760.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2110	
5°	2059	192
15°	1722	481
25°	1288	586
35°	618	387
45°	98	89
55°	17	17
65°	4	6
75°	0	2
85°	0	0
90°	0	



TEST NUMBER: P207813

CATALOG NUMBER: LD4B50D010TE EU4B30509024 4LBNGPH1

CANDELA DISTRIBUTION (FULL):

	0°
0°	2110.5
2.5°	2106.3
5°	2059.4
7.5°	1995.4
10°	1910.1
12.5°	1824.9
15°	1722.5
17.5°	1615.9
20°	1505.1
22.5°	1407.0
25°	1287.6
27.5°	1168.3
30°	1014.8
32.5°	827.2
35°	618.2
37.5°	430.6
40°	277.1
42.5°	170.5
45°	98.1
47.5°	51.2
50°	29.8
52.5°	25.6
55°	17.1
57.5°	12.8
60°	12.8
62.5°	8.5
65°	4.3
67.5°	4.3
70°	4.3
72.5°	4.3
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)