

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P208222

Luminaire Tested: **LD4B50D010TE EU4B30509027 4LBMLI1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P208222
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LD4B50D010TE EU4B30509027 4LBMLI1
Description: PORTFOLIO 4 INCH 50 DEGREE CUTOFF RECESSED DOWNLIGHT
MEDIUM DISTRIBUTION WITH SPECULAR CLEAR TRIM
SINGLE DRIVER D010TE
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 4005.8 lumens
Efficiency: N/A
Efficacy: 68.2 lumens/watt
Spacing Criteria (0/90/45): 0.7 / 0.7 / 0.76
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 58.77
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P208222

CATALOG NUMBER: LD4B50D010TE EU4B30509027 4LBML11

Luminous Intensity Polar Plot





TEST NUMBER: P208222

CATALOG NUMBER: LD4B50D010TE EU4B30509027 4LBMLI1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	114	111	109	107	111	109	107	105	105	103	102	101	100	99	98	97	96	94			
2	109	104	100	97	107	102	99	96	99	96	94	96	94	92	94	92	90	88			
3	104	98	93	89	102	96	92	89	94	90	87	91	88	86	89	87	85	83			
4	99	92	87	83	97	91	86	82	89	85	81	87	83	80	85	82	79	78			
5	94	87	81	77	93	86	81	77	84	79	76	82	78	75	81	77	75	73			
6	90	82	76	72	89	81	76	72	80	75	71	78	74	71	77	73	71	69			
7	86	77	72	68	85	77	71	68	75	71	67	74	70	67	73	69	67	65			
8	82	73	68	64	81	73	67	64	72	67	64	71	66	63	70	66	63	62			
9	79	70	64	60	78	69	64	60	68	63	60	67	63	60	67	63	60	58			
10	75	66	61	57	74	66	61	57	65	60	57	64	60	57	64	60	57	56			

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P208222

CATALOG NUMBER: LD4B50D010TE EU4B30509027 4LBMLI1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	571.8	14.3
10°-20°	1278.3	31.9
20°-30°	1270.9	31.7
30°-40°	692.1	17.3
40°-50°	159.9	4.0
50°-60°	22.5	0.6
60°-70°	8.3	0.2
70°-80°	1.9	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	3121.0	77.9
0°-40°	3813.1	95.2
0°-60°	3995.6	99.7
0°-90°	4005.8	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	4005.8	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	6315	
5°	6184	572
15°	4614	1278
25°	2787	1271
35°	1071	692
45°	184	160
55°	24	23
65°	10	8
75°	0	2
85°	0	0
90°	0	



TEST NUMBER: P208222

CATALOG NUMBER: LD4B50D010TE EU4B30509027 4LBMLI1

CANDELA DISTRIBUTION (FULL):

0°	
0°	6315.1
2.5°	6300.6
5°	6184.3
7.5°	5946.8
10°	5617.2
12.5°	5132.5
15°	4614.0
17.5°	4100.2
20°	3596.2
22.5°	3184.2
25°	2786.8
27.5°	2408.8
30°	1982.3
32.5°	1507.3
35°	1071.1
37.5°	722.1
40°	470.1
42.5°	295.6
45°	184.2
47.5°	106.6
50°	53.3
52.5°	29.1
55°	24.2
57.5°	14.5
60°	14.5
62.5°	9.7
65°	9.7
67.5°	4.8
70°	4.8
72.5°	4.8
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)