

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P207608

Luminaire Tested: **LD4B50D010TE EU4B30509027 4LBMMW1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P207608
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LD4B50D010TE EU4B30509027 4LBMMW1
Description: PORTFOLIO 4 INCH 50 DEGREE CUTOFF RECESSED DOWNLIGHT
MEDIUM DISTRIBUTION WITH MATTE WHITE TRIM
SINGLE DRIVER D010TE
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 3342.3 lumens
Efficiency: N/A
Efficacy: 56.9 lumens/watt
Spacing Criteria (0/90/45): 0.99 / 0.99 / 0.97
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 58.77
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P207608

CATALOG NUMBER: LD4B50D010TE EU4B30509027 4LBMMW1

Luminous Intensity Polar Plot





TEST NUMBER: P207608

CATALOG NUMBER: LD4B50D010TE EU4B30509027 4LBMMW1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	112	108	105	102	109	106	103	100	102	99	97	98	96	94	94	93	91	89			
2	104	98	92	88	102	96	91	87	93	89	85	89	86	83	87	84	81	80			
3	97	89	83	77	95	87	82	77	85	80	76	82	78	74	80	76	73	71			
4	91	81	74	69	89	80	74	69	78	72	68	76	71	67	74	69	66	64			
5	85	75	67	62	83	74	67	62	72	66	61	70	65	61	68	64	60	58			
6	80	69	62	56	78	68	61	56	66	60	56	65	59	55	63	59	55	53			
7	75	64	57	52	74	63	56	51	62	56	51	60	55	51	59	54	50	49			
8	71	59	52	47	69	59	52	47	58	51	47	56	51	47	55	50	47	45			
9	67	55	48	44	66	55	48	44	54	48	44	53	47	43	52	47	43	42			
10	63	52	45	41	62	51	45	41	51	45	40	50	44	40	49	44	40	39			

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P207608

CATALOG NUMBER: LD4B50D010TE EU4B30509027 4LBMMW1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	235.2	7.0
10°-20°	630.5	18.9
20°-30°	838.3	25.1
30°-40°	685.6	20.5
40°-50°	399.4	11.9
50°-60°	264.9	7.9
60°-70°	174.2	5.2
70°-80°	91.9	2.7
80°-90°	22.4	0.7
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1704.0	51.0
0°-40°	2389.6	71.5
0°-60°	3053.8	91.4
0°-90°	3342.3	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	3342.3	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2537	
5°	2508	235
15°	2247	630
25°	1840	838
35°	1094	686
45°	504	399
55°	295	265
65°	174	174
75°	87	92
85°	19	22
90°	0	



TEST NUMBER: P207608

CATALOG NUMBER: LD4B50D010TE EU4B30509027 4LBMMW1

CANDELA DISTRIBUTION (FULL):

	0°
0°	2537.2
2.5°	2532.4
5°	2508.1
7.5°	2450.0
10°	2387.1
12.5°	2329.0
15°	2246.7
17.5°	2154.7
20°	2077.2
22.5°	1970.7
25°	1840.0
27.5°	1699.5
30°	1520.4
32.5°	1307.3
35°	1094.3
37.5°	900.6
40°	731.1
42.5°	600.4
45°	503.6
47.5°	426.1
50°	372.8
52.5°	329.3
55°	295.4
57.5°	261.5
60°	227.6
62.5°	203.4
65°	174.3
67.5°	150.1
70°	125.9
72.5°	106.5
75°	87.2
77.5°	67.8
80°	48.4
82.5°	33.9
85°	19.4
87.5°	4.8
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)