

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P208121

Luminaire Tested: **LD4B50D010TE EU4B30509027 4LBWLI1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P208121
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LD4B50D010TE EU4B30509027 4LBWLI1
Description: PORTFOLIO 4 INCH 60 DEGREE CUTOFF RECESSED DOWNLIGHT
WIDE DISTRIBUTION WITH SPECULAR CLEAR TRIM
SINGLE DRIVER D010TE
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 4228.6 lumens
Efficiency: N/A
Efficacy: 72.0 lumens/watt
Spacing Criteria (0/90/45): 1.29 / 1.29 / 1.18
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 58.77
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P208121

CATALOG NUMBER: LD4B50D010TE EU4B30509027 4LBWLI1

Luminous Intensity Polar Plot





TEST NUMBER: P208121

CATALOG NUMBER: LD4B50D010TE EU4B30509027 4LBWLI1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100	100	100	100
1	113	110	107	105	110	108	105	103	104	102	100	100	98	97	96	95	94	92	92	92	92
2	106	101	97	93	104	99	95	92	96	93	90	93	90	88	90	88	86	84	84	84	84
3	100	93	87	83	98	92	86	82	89	85	81	86	83	80	84	81	78	77	77	77	77
4	94	86	79	75	92	84	79	74	82	77	73	80	76	72	78	75	72	70	70	70	70
5	88	79	72	68	87	78	72	67	76	71	67	74	70	66	73	69	65	64	64	64	64
6	83	73	66	62	82	72	66	61	71	65	61	69	64	60	68	63	60	58	58	58	58
7	78	68	61	56	77	67	61	56	66	60	56	64	59	55	63	59	55	54	54	54	54
8	74	63	56	52	72	62	56	51	61	55	51	60	55	51	59	54	51	49	49	49	49
9	69	59	52	48	68	58	52	47	57	51	47	56	51	47	55	50	47	45	45	45	45
10	66	55	48	44	65	54	48	44	53	48	44	53	47	44	52	47	43	42	42	42	42

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P208121

CATALOG NUMBER: LD4B50D010TE EU4B30509027 4LBWLI1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	253.4	6.0
10°-20°	799.6	18.9
20°-30°	1247.4	29.5
30°-40°	1213.7	28.7
40°-50°	606.2	14.3
50°-60°	93.8	2.2
60°-70°	11.3	0.3
70°-80°	3.1	0.1
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2300.4	54.4
0°-40°	3514.1	83.1
0°-60°	4214.1	99.7
0°-90°	4228.6	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	4228.6	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2591	
5°	2625	253
15°	2824	800
25°	2741	1247
35°	1971	1214
45°	760	606
55°	78	94
65°	10	11
75°	5	3
85°	0	0
90°	0	



TEST NUMBER: P208121

CATALOG NUMBER: LD4B50D010TE EU4B30509027 4LBWLI1

CANDELA DISTRIBUTION (FULL):

	0°
0°	2591.0
2.5°	2600.7
5°	2624.9
7.5°	2663.6
10°	2712.1
12.5°	2775.0
15°	2823.5
17.5°	2862.2
20°	2867.0
22.5°	2833.1
25°	2741.1
27.5°	2605.5
30°	2436.0
32.5°	2222.9
35°	1971.1
37.5°	1695.0
40°	1404.5
42.5°	1094.5
45°	760.3
47.5°	489.1
50°	295.4
52.5°	159.8
55°	77.5
57.5°	33.9
60°	19.4
62.5°	14.5
65°	9.7
67.5°	9.7
70°	4.8
72.5°	4.8
75°	4.8
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)