

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P207809

Luminaire Tested: **LD4B50D010TE EU4B30508030 4LBNGPH1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P207809
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LD4B50D010TE EU4B30508030 4LBNGPH1
Description: PORTFOLIO 4 INCH 50 DEGREE CUTOFF RECESSED DOWNLIGHT
NARROW DISTRIBUTION WITH GRAPHITE HAZE TRIM
SINGLE DRIVER D010TE
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 2435.5 lumens
Efficiency: N/A
Efficacy: 41.4 lumens/watt
Spacing Criteria (0/90/45): 0.86 / 0.86 / 0.88
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 58.77
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P207809

CATALOG NUMBER: LD4B50D010TE EU4B30508030 4LBNGPH1

Luminous Intensity Polar Plot





TEST NUMBER: P207809

CATALOG NUMBER: LD4B50D010TE EU4B30508030 4LBNGPH1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10		0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100		
1	114	111	108	106	111	109	106	104	105	103	101	101	100	98	97	96	95	94		
2	108	103	99	96	106	101	98	95	98	95	93	95	93	91	92	91	89	87		
3	103	96	91	87	101	95	90	87	92	88	85	90	87	84	88	85	83	81		
4	97	90	84	80	96	89	84	80	87	82	79	85	81	78	83	80	77	76		
5	93	84	78	74	91	83	78	74	82	77	73	80	76	73	78	75	72	70		
6	88	79	73	69	86	78	73	69	77	72	68	75	71	68	74	70	67	66		
7	84	74	68	64	82	74	68	64	72	67	64	71	67	63	70	66	63	62		
8	80	70	64	60	78	70	64	60	68	63	60	67	63	59	66	62	59	58		
9	76	66	60	56	75	66	60	56	65	60	56	64	59	56	63	59	56	54		
10	72	63	57	53	71	62	57	53	61	56	53	61	56	53	60	56	52	51		

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P207809

CATALOG NUMBER: LD4B50D010TE EU4B30508030 4LBNGPH1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	265.6	10.9
10°-20°	665.7	27.3
20°-30°	811.3	33.3
30°-40°	535.2	22.0
40°-50°	123.2	5.1
50°-60°	23.6	1.0
60°-70°	8.7	0.4
70°-80°	2.3	0.1
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1742.5	71.5
0°-40°	2277.7	93.5
0°-60°	2424.5	99.5
0°-90°	2435.5	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2435.5	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2921	
5°	2850	266
15°	2384	666
25°	1782	811
35°	856	535
45°	136	123
55°	24	24
65°	6	9
75°	0	2
85°	0	0
90°	0	



TEST NUMBER: P207809

CATALOG NUMBER: LD4B50D010TE EU4B30508030 4LBNGPH1

CANDELA DISTRIBUTION (FULL):

	0°
0°	2920.7
2.5°	2914.8
5°	2849.9
7.5°	2761.4
10°	2643.4
12.5°	2525.4
15°	2383.8
17.5°	2236.3
20°	2082.8
22.5°	1947.1
25°	1781.9
27.5°	1616.7
30°	1404.3
32.5°	1144.7
35°	855.6
37.5°	595.9
40°	383.5
42.5°	236.0
45°	135.7
47.5°	70.8
50°	41.3
52.5°	35.4
55°	23.6
57.5°	17.7
60°	17.7
62.5°	11.8
65°	5.9
67.5°	5.9
70°	5.9
72.5°	5.9
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)