

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P208421

Luminaire Tested: **LD4B50D010TE EU4B30508030 4LBSLI1**

Issue Date: 3/3/2020

**Test Information**

Test Method: LM-41-14  
Report Number: P208421  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)  
Test Lab: INNOVATION CENTER-P3  
Issue Date: 3/3/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: io LED  
Catalog Number: LD4B50D010TE EU4B30508030 4LBSLI1  
Description: PORTFOLIO 4 INCH SHALLOW RECESSED DOWNLIGHT  
SHALLOW DISTRIBUTION WITH SPECULAR CLEAR TRIM  
SINGLE DRIVER D010TE  
Light Source: HIGH LUMEN LED  
Ballast/Driver: ELECTRONIC DRIVER

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 5325.1 lumens  
Efficiency: N/A  
Efficacy: 90.6 lumens/watt  
Spacing Criteria (0/90/45): 0.91 / 0.91 / 1  
Luminous Opening: Point Source (0' x 0' x 0')  
CIE Type: Direct


Input Watts (W): 58.77  
Input Voltage (V): NR  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P208421

CATALOG NUMBER: LD4B50D010TE EU4B30508030 4LBSLI1

### Luminous Intensity Polar Plot





TEST NUMBER: P208421

CATALOG NUMBER: LD4B50D010TE EU4B30508030 4LBSLI1

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	112	108	105	102	109	106	103	101	102	100	98	98	96	95	95	93	92	90																			
2	104	98	93	88	102	96	91	87	93	89	85	90	86	84	87	84	82	80																			
3	97	89	82	77	95	87	81	77	84	79	75	82	78	74	79	76	73	71																			
4	90	81	73	68	88	79	73	68	77	71	67	75	70	66	73	69	65	63																			
5	84	73	66	61	82	72	65	60	70	64	60	69	63	59	67	62	59	57																			
6	79	67	60	54	77	66	59	54	65	58	54	63	58	53	62	57	53	51																			
7	74	62	54	49	72	61	54	49	60	53	49	58	53	48	57	52	48	46																			
8	69	57	50	45	68	57	50	45	55	49	45	54	49	44	53	48	44	42																			
9	65	53	46	41	64	53	46	41	52	45	41	51	45	41	50	44	41	39																			
10	61	50	43	38	60	49	42	38	48	42	38	47	42	38	46	41	37	36																			

**AVERAGE LUMINANCE (cd/sqm):**





TEST NUMBER: P208421

CATALOG NUMBER: LD4B50D010TE EU4B30508030 4LBSLI1

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	344.8	6.5
10°-20°	879.3	16.5
20°-30°	1139.4	21.4
30°-40°	1116.4	21.0
40°-50°	946.3	17.8
50°-60°	620.3	11.6
60°-70°	249.3	4.7
70°-80°	28.5	0.5
80°-90°	0.8	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2363.5	44.4
0°-40°	3479.9	65.3
0°-60°	5046.5	94.8
0°-90°	5325.1	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	5325.1	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	3802	
5°	3702	345
15°	3136	879
25°	2488	1139
35°	1774	1116
45°	1232	946
55°	690	620
65°	242	249
75°	12	29
85°	0	1
90°	0	



TEST NUMBER: P208421

CATALOG NUMBER: LD4B50D010TE EU4B30508030 4LBSLI1

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	3802.3
2.5°	3772.8
5°	3702.1
7.5°	3584.2
10°	3436.8
12.5°	3277.6
15°	3136.2
17.5°	2982.9
20°	2829.6
22.5°	2664.6
25°	2487.7
27.5°	2305.0
30°	2116.3
32.5°	1939.5
35°	1774.4
37.5°	1638.8
40°	1491.4
42.5°	1361.8
45°	1232.1
47.5°	1096.5
50°	960.9
52.5°	825.3
55°	689.7
57.5°	565.9
60°	448.0
62.5°	341.9
65°	241.7
67.5°	159.2
70°	94.3
72.5°	41.3
75°	11.8
77.5°	5.9
80°	5.9
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093







— 0°-180°







(END OF REPORT)