

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P206475

Luminaire Tested: **LD4B50D010TE EU4B30509030 4LBCSMB1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P206475
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LD4B50D010TE EU4B30509030 4LBCSMB1
Description: PORTFOLIO 4 INCH SHALLOW RECESSED DOWNLIGHT
SHALLOW DISTRIBUTION WITH CAST MATTE METALLIC SILVER TRIM
SINGLE DRIVER D010TE
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 4338.6 lumens
Efficiency: N/A
Efficacy: 73.8 lumens/watt
Spacing Criteria (0/90/45): 1.23 / 1.23 / 1.33
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 58.77
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P206475

CATALOG NUMBER: LD4B50D010TE EU4B30509030 4LBCSMB1

Luminous Intensity Polar Plot





TEST NUMBER: P206475

CATALOG NUMBER: LD4B50D010TE EU4B30509030 4LBCSMB1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	111	107	103	100	108	104	101	98	100	98	95	96	94	92	93	91	90	88																			
2	102	95	89	84	99	93	87	83	89	85	81	86	82	79	83	80	77	75																			
3	93	84	77	71	91	83	76	70	80	74	69	77	72	68	74	70	67	65																			
4	86	75	67	61	84	74	66	61	71	65	60	69	63	59	67	62	58	56																			
5	79	67	59	53	77	66	59	53	64	57	52	62	56	52	61	55	51	49																			
6	74	61	53	47	72	60	52	46	58	51	46	57	50	46	55	50	45	43																			
7	68	55	47	41	67	55	47	41	53	46	41	52	45	41	50	45	40	39																			
8	64	51	43	37	62	50	42	37	49	42	37	48	41	37	46	41	36	35																			
9	60	47	39	33	58	46	39	33	45	38	33	44	38	33	43	37	33	31																			
10	56	43	35	30	55	43	35	30	42	35	30	41	34	30	40	34	30	28																			

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P206475

CATALOG NUMBER: LD4B50D010TE EU4B30509030 4LBCSMB1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	173.3	4.0
10°-20°	493.7	11.4
20°-30°	742.1	17.1
30°-40°	880.5	20.3
40°-50°	871.4	20.1
50°-60°	684.5	15.8
60°-70°	383.7	8.8
70°-80°	107.8	2.5
80°-90°	1.7	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1409.0	32.5
0°-40°	2289.6	52.8
0°-60°	3845.4	88.6
0°-90°	4338.6	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	4338.6	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1832	
5°	1829	173
15°	1751	494
25°	1611	742
35°	1412	881
45°	1135	871
55°	771	684
65°	383	384
75°	93	108
85°	0	2
90°	0	



TEST NUMBER: P206475

CATALOG NUMBER: LD4B50D010TE EU4B30509030 4LBCSMB1

CANDELA DISTRIBUTION (FULL):

	0°
0°	1832.0
2.5°	1825.8
5°	1828.9
7.5°	1813.3
10°	1794.7
12.5°	1772.9
15°	1751.1
17.5°	1723.1
20°	1685.8
22.5°	1648.5
25°	1611.1
27.5°	1570.7
30°	1517.8
32.5°	1465.0
35°	1412.1
37.5°	1349.9
40°	1278.3
42.5°	1209.9
45°	1135.3
47.5°	1051.3
50°	964.2
52.5°	864.7
55°	771.4
57.5°	665.6
60°	566.1
62.5°	475.9
65°	382.6
67.5°	301.7
70°	223.9
72.5°	152.4
75°	93.3
77.5°	46.7
80°	12.4
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)