

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P208127

Luminaire Tested: **LD4B50D010TE EU4B30509730 4LBWLI1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P208127
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LD4B50D010TE EU4B30509730 4LBWL1
Description: PORTFOLIO 4 INCH 60 DEGREE CUTOFF RECESSED DOWNLIGHT
WIDE DISTRIBUTION WITH SPECULAR CLEAR TRIM
SINGLE DRIVER D010TE
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 3843.1 lumens
Efficiency: N/A
Efficacy: 65.4 lumens/watt
Spacing Criteria (0/90/45): 1.29 / 1.29 / 1.18
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 58.77
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P208127

CATALOG NUMBER: LD4B50D010TE EU4B30509730 4LBWLI1

Luminous Intensity Polar Plot





TEST NUMBER: P208127

CATALOG NUMBER: LD4B50D010TE EU4B30509730 4LBWLI1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100	100	100	100
1	113	110	107	105	110	108	105	103	104	102	100	100	98	97	96	95	94	92	92	92	92
2	106	101	97	93	104	99	95	92	96	93	90	93	90	88	90	88	86	84	84	84	84
3	100	93	87	83	98	92	86	82	89	85	81	86	83	80	84	81	78	77	77	77	77
4	94	86	79	75	92	84	79	74	82	77	73	80	76	72	78	75	72	70	70	70	70
5	88	79	72	68	87	78	72	67	76	71	67	74	70	66	73	69	65	64	64	64	64
6	83	73	66	62	82	72	66	61	71	65	61	69	64	60	68	63	60	58	58	58	58
7	78	68	61	56	77	67	61	56	66	60	56	64	59	55	63	59	55	54	54	54	54
8	74	63	56	52	72	62	56	51	61	55	51	60	55	51	59	54	51	49	49	49	49
9	69	59	52	48	68	58	52	47	57	51	47	56	51	47	55	50	47	45	45	45	45
10	66	55	48	44	65	54	48	44	53	48	44	53	47	44	52	47	43	42	42	42	42

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P208127

CATALOG NUMBER: LD4B50D010TE EU4B30509730 4LBWLI1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	230.3	6.0
10°-20°	726.7	18.9
20°-30°	1133.7	29.5
30°-40°	1103.1	28.7
40°-50°	550.9	14.3
50°-60°	85.3	2.2
60°-70°	10.3	0.3
70°-80°	2.9	0.1
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2090.7	54.4
0°-40°	3193.7	83.1
0°-60°	3829.9	99.7
0°-90°	3843.1	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	3843.1	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2355	
5°	2386	230
15°	2566	727
25°	2491	1134
35°	1791	1103
45°	691	551
55°	70	85
65°	9	10
75°	4	3
85°	0	0
90°	0	



TEST NUMBER: P208127

CATALOG NUMBER: LD4B50D010TE EU4B30509730 4LBWLI1

CANDELA DISTRIBUTION (FULL):

	0°
0°	2354.8
2.5°	2363.6
5°	2385.6
7.5°	2420.8
10°	2464.8
12.5°	2522.0
15°	2566.1
17.5°	2601.3
20°	2605.7
22.5°	2574.9
25°	2491.2
27.5°	2368.0
30°	2213.9
32.5°	2020.3
35°	1791.4
37.5°	1540.5
40°	1276.4
42.5°	994.7
45°	691.0
47.5°	444.5
50°	268.5
52.5°	145.2
55°	70.4
57.5°	30.8
60°	17.6
62.5°	13.2
65°	8.8
67.5°	8.8
70°	4.4
72.5°	4.4
75°	4.4
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)