

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P208424

Luminaire Tested: **LD4B50D010TE EU4B30508050 4LBSLI1**

Issue Date: 3/3/2020

**Test Information**

Test Method: LM-41-14  
Report Number: P208424  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)  
Test Lab: INNOVATION CENTER-P3  
Issue Date: 3/3/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: io LED  
Catalog Number: LD4B50D010TE EU4B30508050 4LBSLI1  
Description: PORTFOLIO 4 INCH SHALLOW RECESSED DOWNLIGHT  
SHALLOW DISTRIBUTION WITH SPECULAR CLEAR TRIM  
SINGLE DRIVER D010TE  
Light Source: HIGH LUMEN LED  
Ballast/Driver: ELECTRONIC DRIVER

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 5512.8 lumens  
Efficiency: N/A  
Efficacy: 93.8 lumens/watt  
Spacing Criteria (0/90/45): 0.91 / 0.91 / 1  
Luminous Opening: Point Source (0' x 0' x 0')  
CIE Type: Direct


Input Watts (W): 58.77  
Input Voltage (V): NR  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P208424

CATALOG NUMBER: LD4B50D010TE EU4B30508050 4LBSLI1

### Luminous Intensity Polar Plot





TEST NUMBER: P208424

CATALOG NUMBER: LD4B50D010TE EU4B30508050 4LBSLI1

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100	100	100	100
1	112	108	105	102	109	106	103	101	102	100	98	98	96	95	95	93	92	90	90	90	90
2	104	98	93	88	102	96	91	87	93	89	85	90	86	84	87	84	82	80	80	80	80
3	97	89	82	77	95	87	81	77	84	79	75	82	78	74	79	76	73	71	71	71	71
4	90	81	73	68	88	79	73	68	77	71	67	75	70	66	73	69	65	63	63	63	63
5	84	73	66	61	82	72	65	60	70	64	60	69	63	59	67	62	59	57	57	57	57
6	79	67	60	54	77	66	59	54	65	58	54	63	58	53	62	57	53	51	51	51	51
7	74	62	54	49	72	61	54	49	60	53	49	58	53	48	57	52	48	46	46	46	46
8	69	57	50	45	68	57	50	45	55	49	45	54	49	44	53	48	44	42	42	42	42
9	65	53	46	41	64	53	46	41	52	45	41	51	45	41	50	44	41	39	39	39	39
10	61	50	43	38	60	49	42	38	48	42	38	47	42	38	46	41	37	36	36	36	36

**AVERAGE LUMINANCE (cd/sqm):**





TEST NUMBER: P208424

CATALOG NUMBER: LD4B50D010TE EU4B30508050 4LBSLI1

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	356.9	6.5
10°-20°	910.3	16.5
20°-30°	1179.6	21.4
30°-40°	1155.8	21.0
40°-50°	979.6	17.8
50°-60°	642.2	11.6
60°-70°	258.1	4.7
70°-80°	29.5	0.5
80°-90°	0.8	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2446.8	44.4
0°-40°	3602.5	65.3
0°-60°	5224.4	94.8
0°-90°	5512.8	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	5512.8	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	3936	
5°	3833	357
15°	3247	910
25°	2575	1180
35°	1837	1156
45°	1276	980
55°	714	642
65°	250	258
75°	12	30
85°	0	1
90°	0	



TEST NUMBER: P208424

CATALOG NUMBER: LD4B50D010TE EU4B30508050 4LBSLI1

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	3936.3
2.5°	3905.8
5°	3832.6
7.5°	3710.5
10°	3558.0
12.5°	3393.2
15°	3246.7
17.5°	3088.1
20°	2929.4
22.5°	2758.5
25°	2575.4
27.5°	2386.2
30°	2190.9
32.5°	2007.8
35°	1837.0
37.5°	1696.6
40°	1544.0
42.5°	1409.8
45°	1275.5
47.5°	1135.1
50°	994.8
52.5°	854.4
55°	714.0
57.5°	585.9
60°	463.8
62.5°	354.0
65°	250.2
67.5°	164.8
70°	97.6
72.5°	42.7
75°	12.2
77.5°	6.1
80°	6.1
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093







— 0°-180°







(END OF REPORT)