

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P839246

Luminaire Tested: **LD4C25D010 EU4259040 4LBSH**

Issue Date: 2/14/2022



Test Information

Test Method: LM-79-08
Report Number: P839246
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P205729)
Test Lab: INNOVATION CENTER
Issue Date: 2/14/2022
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LD4C25D010 EU4259040 4LBSH
Description: 4 INCH 2500 LUMEN PORTFOLIO LED DOWNLIGHT WITH, 4000K, 90CRI LEDS
AND 4LBS TRIM WITH H FINISH
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 2496.0 lumens
Efficiency: N/A
Efficacy: 79.2 lumens/watt
Spacing Criteria (0/90/45): 1.06 / 1.06 / 1.17
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 31.5
Input Voltage (V):
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P839246

CATALOG NUMBER: LD4C25D010 EU4259040 4LBSH

Luminous Intensity Polar Plot





TEST NUMBER: P839246

CATALOG NUMBER: LD4C25D010 EU4259040 4LBSH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

| | | | | | | | | | | | | | | | | | | | | | |
|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|----|---|
| RF | 20 | | | | 20 | | | | 20 | | | | 20 | | | | 20 | | | | |
| RC | 80 | | | | 70 | | | | 50 | | | | 30 | | | | 10 | | | 0 | |
| RW | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 0 |
| RCR | | | | | | | | | | | | | | | | | | | | | |
| 0 | 119 | 119 | 119 | 119 | 116 | 116 | 116 | 116 | 111 | 111 | 111 | 106 | 106 | 106 | 102 | 102 | 102 | 100 | | | |
| 1 | 111 | 107 | 104 | 101 | 108 | 105 | 102 | 99 | 101 | 98 | 96 | 97 | 95 | 93 | 93 | 92 | 90 | 88 | | | |
| 2 | 102 | 96 | 90 | 85 | 100 | 94 | 88 | 84 | 90 | 86 | 82 | 87 | 83 | 80 | 84 | 81 | 79 | 77 | | | |
| 3 | 95 | 85 | 78 | 73 | 92 | 84 | 77 | 72 | 81 | 75 | 71 | 78 | 74 | 70 | 76 | 72 | 69 | 67 | | | |
| 4 | 87 | 77 | 69 | 63 | 85 | 75 | 68 | 63 | 73 | 67 | 62 | 71 | 65 | 61 | 69 | 64 | 60 | 58 | | | |
| 5 | 81 | 69 | 61 | 55 | 79 | 68 | 61 | 55 | 66 | 60 | 55 | 64 | 59 | 54 | 63 | 58 | 53 | 51 | | | |
| 6 | 75 | 63 | 55 | 49 | 73 | 62 | 54 | 49 | 60 | 54 | 49 | 59 | 53 | 48 | 57 | 52 | 48 | 46 | | | |
| 7 | 70 | 58 | 50 | 44 | 68 | 57 | 49 | 44 | 55 | 49 | 44 | 54 | 48 | 43 | 53 | 47 | 43 | 41 | | | |
| 8 | 65 | 53 | 45 | 40 | 64 | 52 | 45 | 40 | 51 | 44 | 39 | 50 | 44 | 39 | 49 | 43 | 39 | 37 | | | |
| 9 | 61 | 49 | 41 | 36 | 60 | 48 | 41 | 36 | 47 | 40 | 36 | 46 | 40 | 36 | 45 | 40 | 35 | 34 | | | |
| 10 | 58 | 45 | 38 | 33 | 56 | 45 | 38 | 33 | 44 | 37 | 33 | 43 | 37 | 33 | 42 | 37 | 33 | 31 | | | |

AVERAGE LUMINANCE (cd/sqm):

| | |
|-----|--------|
| | 0° |
| 0° | 160373 |
| 5° | 159629 |
| 10° | 156335 |
| 15° | 150653 |
| 20° | 143720 |
| 25° | 135974 |
| 30° | 128255 |
| 35° | 120761 |
| 40° | 113705 |
| 45° | 105999 |
| 50° | 96652 |
| 55° | 85354 |
| 60° | 72262 |
| 65° | 56715 |
| 70° | 40482 |
| 75° | 22167 |
| 80° | 3891 |
| 85° | 0 |



TEST NUMBER: P839246

CATALOG NUMBER: LD4C25D010 EU4259040 4LBSH

ZONAL LUMENS:

| Zone | Lumens | % Fixture |
|-----------|--------|-----------|
| 0°-10° | 122.3 | 4.9 |
| 10°-20° | 332.3 | 13.3 |
| 20°-30° | 461.5 | 18.5 |
| 30°-40° | 503.7 | 20.2 |
| 40°-50° | 469.8 | 18.8 |
| 50°-60° | 356.6 | 14.3 |
| 60°-70° | 195.3 | 7.8 |
| 70°-80° | 53.7 | 2.2 |
| 80°-90° | 0.7 | 0.0 |
| 90°-100° | 0.0 | 0.0 |
| 100°-110° | 0.0 | 0.0 |
| 110°-120° | 0.0 | 0.0 |
| 120°-130° | 0.0 | 0.0 |
| 130°-140° | 0.0 | 0.0 |
| 140°-150° | 0.0 | 0.0 |
| 150°-160° | 0.0 | 0.0 |
| 160°-170° | 0.0 | 0.0 |
| 170°-180° | 0.0 | 0.0 |
| 0°-30° | 916.2 | 36.7 |
| 0°-40° | 1419.8 | 56.9 |
| 0°-60° | 2246.3 | 90.0 |
| 0°-90° | 2496.0 | 100.0 |
| 90°-120° | 0.0 | 0.0 |
| 90°-150° | 0.0 | 0.0 |
| 90°-180° | 0.0 | 0.0 |
| 0°-180° | 2496.0 | 100.0 |

CANDELA DISTRIBUTION:

| | 0° | Flux |
|-----|------|------|
| 0° | 1305 | |
| 5° | 1294 | 122 |
| 15° | 1184 | 332 |
| 25° | 1003 | 462 |
| 35° | 805 | 504 |
| 45° | 610 | 470 |
| 55° | 398 | 357 |
| 65° | 195 | 195 |
| 75° | 47 | 54 |
| 85° | 0 | 1 |
| 90° | 0 | |



TEST NUMBER: P839246

CATALOG NUMBER: LD4C25D010 EU4259040 4LBSH

CANDELA DISTRIBUTION (FULL):

| 0° | |
|-------|--------|
| 0° | 1305.4 |
| 2.5° | 1305.4 |
| 5° | 1294.4 |
| 7.5° | 1278.0 |
| 10° | 1253.2 |
| 12.5° | 1220.2 |
| 15° | 1184.5 |
| 17.5° | 1140.5 |
| 20° | 1099.3 |
| 22.5° | 1049.8 |
| 25° | 1003.1 |
| 27.5° | 956.4 |
| 30° | 904.1 |
| 32.5° | 854.7 |
| 35° | 805.2 |
| 37.5° | 755.8 |
| 40° | 709.0 |
| 42.5° | 659.6 |
| 45° | 610.1 |
| 47.5° | 560.6 |
| 50° | 505.7 |
| 52.5° | 453.4 |
| 55° | 398.5 |
| 57.5° | 346.3 |
| 60° | 294.1 |
| 62.5° | 241.9 |
| 65° | 195.1 |
| 67.5° | 151.1 |
| 70° | 112.7 |
| 72.5° | 77.0 |
| 75° | 46.7 |
| 77.5° | 22.0 |
| 80° | 5.5 |
| 82.5° | 0.0 |
| 85° | 0.0 |
| 87.5° | 0.0 |
| 90° | 0.0 |



Report Generated By 670246072 / DESKTOP-50001EG





— 0°-180°







(END OF REPORT)