

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P839294

Luminaire Tested: **LD4C40D010 EU4409050 4LBSH**

Issue Date: 2/14/2022

Test Information

Test Method: LM-79-08
Report Number: P839294
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P205729)
Test Lab: INNOVATION CENTER
Issue Date: 2/14/2022
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LD4C40D010 EU4409050 4LBSH
Description: 4 INCH 4000 LUMEN PORTFOLIO LED DOWNLIGHT WITH, 5000K, 90CRI LEDS
AND 4LBS TRIM WITH H FINISH
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 4097.0 lumens
Efficiency: N/A
Efficacy: 87.2 lumens/watt
Spacing Criteria (0/90/45): 1.06 / 1.06 / 1.17
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 47
Input Voltage (V):
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P839294

CATALOG NUMBER: LD4C40D010 EU4409050 4LBSH

Luminous Intensity Polar Plot





TEST NUMBER: P839294

CATALOG NUMBER: LD4C40D010 EU4409050 4LBSH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	111	107	104	101	108	105	102	99	101	98	96	97	95	93	93	92	90	88			
2	102	96	90	85	100	94	88	84	90	86	82	87	83	80	84	81	79	77			
3	95	85	78	73	92	84	77	72	81	75	71	78	74	70	76	72	69	67			
4	87	77	69	63	85	75	68	63	73	67	62	71	65	61	69	64	60	58			
5	81	69	61	55	79	68	61	55	66	60	55	64	59	54	63	58	53	51			
6	75	63	55	49	73	62	54	49	60	54	49	59	53	48	57	52	48	46			
7	70	58	50	44	68	57	49	44	55	49	44	54	48	43	53	47	43	41			
8	65	53	45	40	64	52	45	40	51	44	39	50	44	39	49	43	39	37			
9	61	49	41	36	60	48	41	36	47	40	36	46	40	36	45	40	35	34			
10	58	45	38	33	56	45	38	33	44	37	33	43	37	33	42	37	33	31			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	263238
5°	262024
10°	256608
15°	247290
20°	235904
25°	223189
30°	210533
35°	198224
40°	186643
45°	173984
50°	158654
55°	140101
60°	118603
65°	93110
70°	66452
75°	36407
80°	6438
85°	0



TEST NUMBER: P839294

CATALOG NUMBER: LD4C40D010 EU4409050 4LBSH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	200.7	4.9
10°-20°	545.5	13.3
20°-30°	757.6	18.5
30°-40°	826.7	20.2
40°-50°	771.2	18.8
50°-60°	585.3	14.3
60°-70°	320.5	7.8
70°-80°	88.2	2.2
80°-90°	1.2	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1503.8	36.7
0°-40°	2330.5	56.9
0°-60°	3687.0	90.0
0°-90°	4097.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	4097.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2143	
5°	2125	201
15°	1944	546
25°	1646	758
35°	1322	827
45°	1001	771
55°	654	585
65°	320	321
75°	77	88
85°	0	1
90°	0	



TEST NUMBER: P839294

CATALOG NUMBER: LD4C40D010 EU4409050 4LBSH

CANDELA DISTRIBUTION (FULL):

	0°
0°	2142.7
2.5°	2142.7
5°	2124.7
7.5°	2097.7
10°	2057.0
12.5°	2002.9
15°	1944.3
17.5°	1872.1
20°	1804.4
22.5°	1723.2
25°	1646.5
27.5°	1569.9
30°	1484.1
32.5°	1402.9
35°	1321.7
37.5°	1240.5
40°	1163.8
42.5°	1082.6
45°	1001.4
47.5°	920.2
50°	830.1
52.5°	744.3
55°	654.1
57.5°	568.3
60°	482.7
62.5°	397.0
65°	320.3
67.5°	248.1
70°	185.0
72.5°	126.3
75°	76.7
77.5°	36.1
80°	9.1
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-50001EG





— 0°-180°







(END OF REPORT)