

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P839519

Luminaire Tested: **LD6C60D010 EU6609040 6LCSQWLI**

Issue Date: 6/29/2023

Test Information

Test Method: LM-79-08
Report Number: P839519
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2105-247-17)
Test Lab: INNOVATION CENTER
Issue Date: 6/29/2023
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LD6C60D010 EU6609040 6LCSQWLI
Description: 6 INCH 6000 LUMEN PORTFOLIO LED DOWNLIGHT WITH, 4000K, 90CRI LEDS
AND 6LCSQW TRIM WITH LI FINISH
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 6534.0 lumens
Efficiency: N/A
Efficacy: 90.8 lumens/watt
Spacing Criteria (0/90/45): 1.19 / 1.19 / 1.29
Luminous Opening: Rectangular (W 0.5' x L: 0.5' x H: 0')
CIE Type: Direct

Input Watts (W): 72
Input Voltage (V):
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P839519

CATALOG NUMBER: LD6C60D010 EU6609040 6LCSQWLI

Luminous Intensity Polar Plot





TEST NUMBER: P839519

CATALOG NUMBER: LD6C60D010 EU6609040 6LCSQWLI

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			100
1	111	107	103	100	108	105	101	98	100	98	95	97	94	92	93	91	90	88			88
2	102	95	89	85	100	93	88	84	90	86	82	87	83	80	84	81	78	76			76
3	94	85	78	72	92	84	77	72	81	75	71	78	73	69	76	72	68	66			66
4	87	77	69	63	85	75	68	62	73	67	62	71	65	61	69	64	60	58			58
5	81	69	61	55	79	68	60	55	66	59	54	64	58	54	62	57	53	51			51
6	75	63	55	49	73	62	54	49	60	53	48	59	52	48	57	52	47	46			46
7	70	57	49	44	68	57	49	43	55	48	43	54	47	43	52	47	43	41			41
8	65	53	45	39	64	52	44	39	51	44	39	49	43	39	48	43	38	37			37
9	61	48	41	36	60	48	41	35	47	40	35	46	40	35	45	39	35	33			33
10	57	45	37	32	56	44	37	32	43	37	32	42	36	32	42	36	32	30			30

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	131940
5°	131726
10°	131007
15°	129493
20°	127138
25°	124387
30°	121427
35°	117963
40°	113214
45°	105017
50°	90474
55°	72168
60°	56188
65°	42055
70°	30515
75°	24205
80°	22662
85°	22576



TEST NUMBER: P839519

CATALOG NUMBER: LD6C60D010 EU6609040 6LCSQWLI

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	289.3	4.4
10°-20°	818.1	12.5
20°-30°	1205.6	18.5
30°-40°	1400.6	21.4
40°-50°	1316.5	20.1
50°-60°	871.4	13.3
60°-70°	419.9	6.4
70°-80°	162.0	2.5
80°-90°	50.5	0.8
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2313.1	35.4
0°-40°	3713.7	56.8
0°-60°	5901.6	90.3
0°-90°	6534.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	6534.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	3064	
5°	3048	289
15°	2905	818
25°	2618	1206
35°	2244	1401
45°	1725	1316
55°	961	871
65°	413	420
75°	146	162
85°	46	51
90°	0	



TEST NUMBER: P839519

CATALOG NUMBER: LD6C60D010 EU6609040 6LCSQWLI

CANDELA DISTRIBUTION (FULL):

0°	
0°	3064.4
2.5°	3061.6
5°	3047.8
7.5°	3027.0
10°	2996.5
12.5°	2954.9
15°	2905.1
17.5°	2844.1
20°	2774.8
22.5°	2698.6
25°	2618.3
27.5°	2532.4
30°	2442.4
32.5°	2346.8
35°	2244.3
37.5°	2132.0
40°	2014.3
42.5°	1881.3
45°	1724.7
47.5°	1547.4
50°	1350.7
52.5°	1151.2
55°	961.4
57.5°	798.0
60°	652.5
62.5°	522.3
65°	412.8
67.5°	320.0
70°	242.4
72.5°	184.3
75°	145.5
77.5°	117.8
80°	91.4
82.5°	67.9
85°	45.7
87.5°	26.3
90°	0.0



Report Generated By 670246072 / DESKTOP-50001EG





— 0°-180°







(END OF REPORT)