

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P839572

Luminaire Tested: **LDS4C05D010 EU4059035 4LBSH**

Issue Date: 8/24/2022



Test Information

Test Method: LM-79-08
Report Number: P839572
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P205729)
Test Lab: INNOVATION CENTER
Issue Date: 8/24/2022
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LDS4C05D010 EU4059035 4LBSH
Description: 4 INCH 500 LUMEN PORTFOLIO LED DOWNLIGHT WITH, 3500K, 90CRI LEDS AND 4LBS TRIM WITH H FINISH
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 651.0 lumens
Efficiency: N/A
Efficacy: 90.4 lumens/watt
Spacing Criteria (0/90/45): 1.06 / 1.06 / 1.17
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 7.2
Input Voltage (V):
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P839572

CATALOG NUMBER: LDS4C05D010 EU4059035 4LBSH

Luminous Intensity Polar Plot





TEST NUMBER: P839572

CATALOG NUMBER: LDS4C05D010 EU4059035 4LBSH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	111	107	104	101	108	105	102	99	101	98	96	97	95	93	93	92	90	88			
2	102	96	90	85	100	94	88	84	90	86	82	87	83	80	84	81	79	77			
3	95	85	78	73	92	84	77	72	81	75	71	78	74	70	76	72	69	67			
4	87	77	69	63	85	75	68	63	73	67	62	71	65	61	69	64	60	58			
5	81	69	61	55	79	68	61	55	66	60	55	64	59	54	63	58	53	51			
6	75	63	55	49	73	62	54	49	60	54	49	59	53	48	57	52	48	46			
7	70	58	50	44	68	57	49	44	55	49	44	54	48	43	53	47	43	41			
8	65	53	45	40	64	52	45	40	51	44	39	50	44	39	49	43	39	37			
9	61	49	41	36	60	48	41	36	47	40	36	46	40	36	45	40	35	34			
10	58	45	38	33	56	45	38	33	44	37	33	43	37	33	42	37	33	31			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	41832
5°	41634
10°	40780
15°	39288
20°	37483
25°	35461
30°	33450
35°	31495
40°	29653
45°	27642
50°	25210
55°	22254
60°	18846
65°	14796
70°	10560
75°	5791
80°	990
85°	0



TEST NUMBER: P839572

CATALOG NUMBER: LDS4C05D010 EU4059035 4LSBH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	31.9	4.9
10°-20°	86.7	13.3
20°-30°	120.4	18.5
30°-40°	131.4	20.2
40°-50°	122.5	18.8
50°-60°	93.0	14.3
60°-70°	50.9	7.8
70°-80°	14.0	2.2
80°-90°	0.2	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	238.9	36.7
0°-40°	370.3	56.9
0°-60°	585.8	90.0
0°-90°	651.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	651.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	340	
5°	338	32
15°	309	87
25°	262	120
35°	210	131
45°	159	123
55°	104	93
65°	51	51
75°	12	14
85°	0	0
90°	0	



TEST NUMBER: P839572

CATALOG NUMBER: LDS4C05D010 EU4059035 4LBSH

CANDELA DISTRIBUTION (FULL):

	0°
0°	340.5
2.5°	340.5
5°	337.6
7.5°	333.3
10°	326.9
12.5°	318.3
15°	308.9
17.5°	297.5
20°	286.7
22.5°	273.8
25°	261.6
27.5°	249.4
30°	235.8
32.5°	222.9
35°	210.0
37.5°	197.1
40°	184.9
42.5°	172.0
45°	159.1
47.5°	146.2
50°	131.9
52.5°	118.3
55°	103.9
57.5°	90.3
60°	76.7
62.5°	63.1
65°	50.9
67.5°	39.4
70°	29.4
72.5°	20.1
75°	12.2
77.5°	5.7
80°	1.4
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-50001EG





— 0°-180°







(END OF REPORT)