

Scaled data based on original data using  
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State  
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P839575

Luminaire Tested: **LDS4C05D010 EU4059035 4LBSWMH**

Issue Date: 8/24/2022



**Test Information**

Test Method: LM-79-08  
Report Number: P839575  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P205729)  
Test Lab: INNOVATION CENTER  
Issue Date: 8/24/2022  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: PORTFOLIO  
Catalog Number: LDS4C05D010 EU4059035 4LBSWMH  
Description: 4 INCH 500 LUMEN PORTFOLIO LED DOWNLIGHT WITH, 3500K, 90CRI LEDS AND 4LBS TRIM WITH WMH FINISH  
Light Source: -  
Ballast/Driver: -


**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 578.0 lumens  
Efficiency: N/A  
Efficacy: 80.3 lumens/watt  
Spacing Criteria (0/90/45): 1.06 / 1.06 / 1.17  
Luminous Opening: Circular (Dia: 0.33' x H: 0')  
CIE Type: Direct  
  
Input Watts (W): 7.2  
Input Voltage (V):  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT

TEST NUMBER: P839575

CATALOG NUMBER: LDS4C05D010 EU4059035 4LBSWMH

### Luminous Intensity Polar Plot





TEST NUMBER: P839575

CATALOG NUMBER: LDS4C05D010 EU4059035 4LBSWMH

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	111	107	104	101	108	105	102	99	101	98	96	97	95	93	93	92	90	88			
2	102	96	90	85	100	94	88	84	90	86	82	87	83	80	84	81	79	77			
3	95	85	78	73	92	84	77	72	81	75	71	78	74	70	76	72	69	67			
4	87	77	69	63	85	75	68	63	73	67	62	71	65	61	69	64	60	58			
5	81	69	61	55	79	68	61	55	66	60	55	64	59	54	63	58	53	51			
6	75	63	55	49	73	62	54	49	60	54	49	59	53	48	57	52	48	46			
7	70	58	50	44	68	57	49	44	55	49	44	54	48	43	53	47	43	41			
8	65	53	45	40	64	52	45	40	51	44	39	50	44	39	49	43	39	37			
9	61	49	41	36	60	48	41	36	47	40	36	46	40	36	45	40	35	34			
10	58	45	38	33	56	45	38	33	44	37	33	43	37	33	42	37	33	31			

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	37139
5°	36960
10°	36202
15°	34887
20°	33286
25°	31489
30°	29705
35°	27971
40°	26333
45°	24550
50°	22381
55°	19770
60°	16733
65°	13139
70°	9375
75°	5126
80°	920
85°	0



TEST NUMBER: P839575

CATALOG NUMBER: LDS4C05D010 EU4059035 4LBSWMH

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	28.3	4.9
10°-20°	77.0	13.3
20°-30°	106.9	18.5
30°-40°	116.6	20.2
40°-50°	108.8	18.8
50°-60°	82.6	14.3
60°-70°	45.2	7.8
70°-80°	12.4	2.2
80°-90°	0.2	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	212.2	36.7
0°-40°	328.8	56.9
0°-60°	520.2	90.0
0°-90°	578.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	578.0	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	302	
5°	300	28
15°	274	77
25°	232	107
35°	186	117
45°	141	109
55°	92	83
65°	45	45
75°	11	12
85°	0	0
90°	0	



TEST NUMBER: P839575

CATALOG NUMBER: LDS4C05D010 EU4059035 4LBSWMH

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	302.3
2.5°	302.3
5°	299.7
7.5°	295.9
10°	290.2
12.5°	282.6
15°	274.3
17.5°	264.1
20°	254.6
22.5°	243.1
25°	232.3
27.5°	221.5
30°	209.4
32.5°	197.9
35°	186.5
37.5°	175.0
40°	164.2
42.5°	152.7
45°	141.3
47.5°	129.8
50°	117.1
52.5°	105.0
55°	92.3
57.5°	80.2
60°	68.1
62.5°	56.0
65°	45.2
67.5°	35.0
70°	26.1
72.5°	17.8
75°	10.8
77.5°	5.1
80°	1.3
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-50001EG







— 0°-180°







(END OF REPORT)