

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P839581

Luminaire Tested: **LDS4C05D010 EU4059040 4LBSGPH**

Issue Date: 8/24/2022



Test Information

Test Method: LM-79-08
Report Number: P839581
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2105-247-18)
Test Lab: INNOVATION CENTER
Issue Date: 8/24/2022
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LDS4C05D010 EU4059040 4LBSGPH
Description: 4 INCH 500 LUMEN PORTFOLIO LED DOWNLIGHT WITH, 4000K, 90CRI LEDS AND 4LBS TRIM WITH GPH FINISH
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 432.0 lumens
Efficiency: N/A
Efficacy: 60.0 lumens/watt
Spacing Criteria (0/90/45): 1.16 / 1.16 / 1.25
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 7.2
Input Voltage (V):
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P839581

CATALOG NUMBER: LDS4C05D010 EU4059040 4LBSGPH

Luminous Intensity Polar Plot





TEST NUMBER: P839581

CATALOG NUMBER: LDS4C05D010 EU4059040 4LBSGPH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100	100	100	100
1	112	108	105	102	109	106	103	100	102	99	97	98	96	94	94	93	92	90	90	90	90
2	104	97	92	88	101	96	91	87	92	88	85	89	86	83	86	83	81	79	79	79	79
3	96	88	81	76	94	86	80	75	83	78	74	81	76	73	78	75	72	70	70	70	70
4	89	79	72	66	87	78	71	66	76	70	65	73	68	64	71	67	63	62	62	62	62
5	83	72	64	59	81	71	64	58	69	63	58	67	61	57	65	60	57	55	55	55	55
6	77	66	58	52	75	65	57	52	63	56	52	61	56	51	60	55	51	49	49	49	49
7	72	60	52	47	70	59	52	47	58	51	46	56	50	46	55	50	46	44	44	44	44
8	67	55	47	42	66	54	47	42	53	47	42	52	46	42	51	46	41	40	40	40	40
9	63	51	43	38	62	50	43	38	49	43	38	48	42	38	47	42	38	36	36	36	36
10	59	47	40	35	58	47	40	35	46	39	35	45	39	35	44	39	35	33	33	33	33

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	27863
5°	27772
10°	27470
15°	26989
20°	26396
25°	25687
30°	24882
35°	23921
40°	22709
45°	20640
50°	17048
55°	12551
60°	8526
65°	5000
70°	1976
75°	427
80°	566
85°	987



TEST NUMBER: P839581

CATALOG NUMBER: LDS4C05D010 EU4059040 4LBSGPH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	21.3	4.9
10°-20°	59.8	13.8
20°-30°	87.2	20.2
30°-40°	99.5	23.0
40°-50°	90.4	20.9
50°-60°	53.3	12.3
60°-70°	17.9	4.1
70°-80°	1.8	0.4
80°-90°	0.7	0.2
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	168.3	39.0
0°-40°	267.8	62.0
0°-60°	411.6	95.3
0°-90°	432.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	432.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	227	
5°	225	21
15°	212	60
25°	190	87
35°	160	100
45°	119	90
55°	59	53
65°	17	18
75°	1	2
85°	1	1
90°	0	



TEST NUMBER: P839581

CATALOG NUMBER: LDS4C05D010 EU4059040 4LBSGPH

CANDELA DISTRIBUTION (FULL):

0°	
0°	226.8
2.5°	226.5
5°	225.2
7.5°	223.1
10°	220.2
12.5°	216.4
15°	212.2
17.5°	207.3
20°	201.9
22.5°	195.9
25°	189.5
27.5°	182.5
30°	175.4
32.5°	167.5
35°	159.5
37.5°	150.7
40°	141.6
42.5°	131.0
45°	118.8
47.5°	104.8
50°	89.2
52.5°	73.5
55°	58.6
57.5°	45.9
60°	34.7
62.5°	25.1
65°	17.2
67.5°	10.5
70°	5.5
72.5°	2.1
75°	0.9
77.5°	0.9
80°	0.8
82.5°	0.7
85°	0.7
87.5°	0.6
90°	0.0



Report Generated By 670246072 / DESKTOP-50001EG





— 0°-180°







(END OF REPORT)