

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P839594

Luminaire Tested: **LDS4C05D010 EU4059050 4LBSWH**

Issue Date: 8/24/2022



Test Information

Test Method: LM-79-08
Report Number: P839594
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P205729)
Test Lab: INNOVATION CENTER
Issue Date: 8/24/2022
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LDS4C05D010 EU4059050 4LBSWH
Description: 4 INCH 500 LUMEN PORTFOLIO LED DOWNLIGHT WITH, 5000K, 90CRI LEDS AND 4LBS TRIM WITH WH FINISH
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 619.0 lumens
Efficiency: N/A
Efficacy: 86.0 lumens/watt
Spacing Criteria (0/90/45): 1.06 / 1.06 / 1.17
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 7.2
Input Voltage (V):
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P839594

CATALOG NUMBER: LDS4C05D010 EU4059050 4LBSWH

Luminous Intensity Polar Plot





TEST NUMBER: P839594

CATALOG NUMBER: LDS4C05D010 EU4059050 4LBSWH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	111	107	104	101	108	105	102	99	101	98	96	97	95	93	93	92	90	88			
2	102	96	90	85	100	94	88	84	90	86	82	87	83	80	84	81	79	77			
3	95	85	78	73	92	84	77	72	81	75	71	78	74	70	76	72	69	67			
4	87	77	69	63	85	75	68	63	73	67	62	71	65	61	69	64	60	58			
5	81	69	61	55	79	68	61	55	66	60	55	64	59	54	63	58	53	51			
6	75	63	55	49	73	62	54	49	60	54	48	59	53	48	57	52	48	46			
7	70	58	50	44	68	57	49	44	55	49	44	54	48	43	53	47	43	41			
8	65	53	45	40	64	52	45	40	51	44	39	50	44	39	49	43	39	37			
9	61	49	41	36	60	48	41	36	47	40	36	46	40	36	45	40	35	34			
10	58	45	38	33	56	45	38	33	44	37	33	43	37	33	42	37	33	31			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	39768
5°	39587
10°	38772
15°	37355
20°	35639
25°	33726
30°	31805
35°	29950
40°	28194
45°	26287
50°	23967
55°	21162
60°	17912
65°	14070
70°	10058
75°	5506
80°	990
85°	0



TEST NUMBER: P839594

CATALOG NUMBER: LDS4C05D010 EU4059050 4LBSWH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	30.3	4.9
10°-20°	82.4	13.3
20°-30°	114.5	18.5
30°-40°	124.9	20.2
40°-50°	116.5	18.8
50°-60°	88.4	14.3
60°-70°	48.4	7.8
70°-80°	13.3	2.2
80°-90°	0.2	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	227.2	36.7
0°-40°	352.1	56.9
0°-60°	557.1	90.0
0°-90°	619.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	619.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	324	
5°	321	30
15°	294	82
25°	249	114
35°	200	125
45°	151	117
55°	99	88
65°	48	48
75°	12	13
85°	0	0
90°	0	



TEST NUMBER: P839594

CATALOG NUMBER: LDS4C05D010 EU4059050 4LBSWH

CANDELA DISTRIBUTION (FULL):

	0°
0°	323.7
2.5°	323.7
5°	321.0
7.5°	316.9
10°	310.8
12.5°	302.6
15°	293.7
17.5°	282.9
20°	272.6
22.5°	260.3
25°	248.8
27.5°	237.2
30°	224.2
32.5°	212.0
35°	199.7
37.5°	187.4
40°	175.8
42.5°	163.6
45°	151.3
47.5°	139.0
50°	125.4
52.5°	112.5
55°	98.8
57.5°	85.9
60°	72.9
62.5°	60.0
65°	48.4
67.5°	37.5
70°	28.0
72.5°	19.1
75°	11.6
77.5°	5.4
80°	1.4
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-50001EG





— 0°-180°







(END OF REPORT)