

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P839605

Luminaire Tested: **LDS4C08D010 EU4089027 4LBSWMH**

Issue Date: 8/24/2022



Test Information

Test Method: LM-79-08
Report Number: P839605
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P205729)
Test Lab: INNOVATION CENTER
Issue Date: 8/24/2022
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LDS4C08D010 EU4089027 4LBSWMH
Description: 4 INCH 800 LUMEN PORTFOLIO LED DOWNLIGHT WITH, 2700K, 90CRI LEDS AND 4LBS TRIM WITH WMH FINISH
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 738.0 lumens
Efficiency: N/A
Efficacy: 74.5 lumens/watt
Spacing Criteria (0/90/45): 1.06 / 1.06 / 1.17
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 9.9
Input Voltage (V):
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P839605

CATALOG NUMBER: LDS4C08D010 EU4089027 4LBSWMH

Luminous Intensity Polar Plot





TEST NUMBER: P839605

CATALOG NUMBER: LDS4C08D010 EU4089027 4LBSWMH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	111	107	104	101	108	105	102	99	101	98	96	97	95	93	93	92	90	88			
2	102	96	90	85	100	94	88	84	90	86	82	87	83	80	84	81	79	77			
3	95	85	78	73	92	84	77	72	81	75	71	78	74	70	76	72	69	67			
4	87	77	69	63	85	75	68	63	73	67	62	71	65	61	69	64	60	58			
5	81	69	61	55	79	68	61	55	66	60	55	64	59	54	63	58	53	51			
6	75	63	55	49	73	62	54	49	60	54	49	59	53	48	57	52	48	46			
7	70	58	50	44	68	57	49	44	55	49	44	54	48	43	53	47	43	41			
8	65	53	45	40	64	52	45	40	51	44	39	50	44	39	49	43	39	37			
9	61	49	41	36	60	48	41	36	47	40	36	46	40	36	45	40	35	34			
10	58	45	38	33	56	45	38	33	44	37	33	43	37	33	42	37	33	31			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	47421
5°	47196
10°	46219
15°	44541
20°	42490
25°	40205
30°	37919
35°	35709
40°	33614
45°	31343
50°	28573
55°	25231
60°	21352
65°	16773
70°	11961
75°	6550
80°	1132
85°	0



TEST NUMBER: P839605

CATALOG NUMBER: LDS4C08D010 EU4089027 4LBSWMH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	36.2	4.9
10°-20°	98.3	13.3
20°-30°	136.5	18.5
30°-40°	148.9	20.2
40°-50°	138.9	18.8
50°-60°	105.4	14.3
60°-70°	57.7	7.8
70°-80°	15.9	2.2
80°-90°	0.2	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	270.9	36.7
0°-40°	419.8	56.9
0°-60°	664.2	90.0
0°-90°	738.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	738.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	386	
5°	383	36
15°	350	98
25°	297	136
35°	238	149
45°	180	139
55°	118	105
65°	58	58
75°	14	16
85°	0	0
90°	0	



TEST NUMBER: P839605

CATALOG NUMBER: LDS4C08D010 EU4089027 4LBSWMH

CANDELA DISTRIBUTION (FULL):

	0°
0°	386.0
2.5°	386.0
5°	382.7
7.5°	377.9
10°	370.5
12.5°	360.8
15°	350.2
17.5°	337.2
20°	325.0
22.5°	310.4
25°	296.6
27.5°	282.8
30°	267.3
32.5°	252.7
35°	238.1
37.5°	223.5
40°	209.6
42.5°	195.0
45°	180.4
47.5°	165.8
50°	149.5
52.5°	134.1
55°	117.8
57.5°	102.4
60°	86.9
62.5°	71.5
65°	57.7
67.5°	44.7
70°	33.3
72.5°	22.8
75°	13.8
77.5°	6.5
80°	1.6
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-50001EG





— 0°-180°







(END OF REPORT)