

Scaled data based on original data using  
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State  
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P839645

Luminaire Tested: **LDS4C08D010 EU4089050 4LBSWMH**

Issue Date: 8/24/2022



**Test Information**

Test Method: LM-79-08  
Report Number: P839645  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P205729)  
Test Lab: INNOVATION CENTER  
Issue Date: 8/24/2022  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: PORTFOLIO  
Catalog Number: LDS4C08D010 EU4089050 4LBSWMH  
Description: 4 INCH 800 LUMEN PORTFOLIO LED DOWNLIGHT WITH, 5000K, 90CRI LEDS AND 4LBS TRIM WITH WMH FINISH  
Light Source: -  
Ballast/Driver: -

**Summary**


Lumens per Lamp: N/A  
Luminaire Lumens: 795.0 lumens  
Efficiency: N/A  
Efficacy: 80.3 lumens/watt  
Spacing Criteria (0/90/45): 1.06 / 1.06 / 1.17  
Luminous Opening: Circular (Dia: 0.33' x H: 0')  
CIE Type: Direct

Input Watts (W): 9.9  
Input Voltage (V):  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT

TEST NUMBER: P839645

CATALOG NUMBER: LDS4C08D010 EU4089050 4LBSWMH

### Luminous Intensity Polar Plot





TEST NUMBER: P839645

CATALOG NUMBER: LDS4C08D010 EU4089050 4LBSWMH

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20				
RC	80				70				50				30				10		0		
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	111	107	104	101	108	105	102	99	101	98	96	97	95	93	93	92	90	88			
2	102	96	90	85	100	94	88	84	90	86	82	87	83	80	84	81	79	77			
3	95	85	78	73	92	84	77	72	81	75	71	78	74	70	76	72	69	67			
4	87	77	69	63	85	75	68	63	73	67	62	71	65	61	69	64	60	58			
5	81	69	61	55	79	68	61	55	66	60	55	64	59	54	63	58	53	51			
6	75	63	55	49	73	62	54	49	60	54	49	59	53	48	57	52	48	46			
7	70	58	50	44	68	57	49	44	55	49	44	54	48	43	53	47	43	41			
8	65	53	45	40	64	52	45	40	51	44	39	50	44	39	49	43	39	37			
9	61	49	41	36	60	48	41	36	47	40	36	46	40	36	45	40	35	34			
10	58	45	38	33	56	45	38	33	44	37	33	43	37	33	42	37	33	31			

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	51082
5°	50846
10°	49800
15°	47988
20°	45771
25°	43309
30°	40855
35°	38469
40°	36212
45°	33758
50°	30790
55°	27181
60°	23023
65°	18081
70°	12895
75°	7073
80°	1273
85°	0



TEST NUMBER: P839645

CATALOG NUMBER: LDS4C08D010 EU4089050 4LBSWMH

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	38.9	4.9
10°-20°	105.9	13.3
20°-30°	147.0	18.5
30°-40°	160.4	20.2
40°-50°	149.7	18.8
50°-60°	113.6	14.3
60°-70°	62.2	7.8
70°-80°	17.1	2.2
80°-90°	0.2	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	291.8	36.7
0°-40°	452.2	56.9
0°-60°	715.5	90.0
0°-90°	795.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	795.0	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	416	
5°	412	39
15°	377	106
25°	320	147
35°	256	160
45°	194	150
55°	127	114
65°	62	62
75°	15	17
85°	0	0
90°	0	



TEST NUMBER: P839645

CATALOG NUMBER: LDS4C08D010 EU4089050 4LBSWMH

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	415.8
2.5°	415.8
5°	412.3
7.5°	407.0
10°	399.2
12.5°	388.7
15°	377.3
17.5°	363.3
20°	350.1
22.5°	334.4
25°	319.5
27.5°	304.6
30°	288.0
32.5°	272.2
35°	256.5
37.5°	240.7
40°	225.8
42.5°	210.1
45°	194.3
47.5°	178.6
50°	161.1
52.5°	144.4
55°	126.9
57.5°	110.3
60°	93.7
62.5°	77.0
65°	62.2
67.5°	48.1
70°	35.9
72.5°	24.5
75°	14.9
77.5°	7.0
80°	1.8
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-50001EG







— 0°-180°







(END OF REPORT)