

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P839714

Luminaire Tested: **LDS4C10D010 EU4109030 4LBSWH**

Issue Date: 8/24/2022



Test Information

Test Method: LM-79-08
Report Number: P839714
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P205729)
Test Lab: INNOVATION CENTER
Issue Date: 8/24/2022
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LDS4C10D010 EU4109030 4LBSWH
Description: 4 INCH 1000 LUMEN PORTFOLIO LED DOWNLIGHT WITH, 3000K, 90CRI LEDS
AND 4LBS TRIM WITH WH FINISH
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 921.0 lumens
Efficiency: N/A
Efficacy: 94.0 lumens/watt
Spacing Criteria (0/90/45): 1.06 / 1.06 / 1.17
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 9.8
Input Voltage (V):
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P839714

CATALOG NUMBER: LDS4C10D010 EU4109030 4LBSWH

Luminous Intensity Polar Plot





TEST NUMBER: P839714

CATALOG NUMBER: LDS4C10D010 EU4109030 4LBSWH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	111	107	104	101	108	105	102	99	101	98	96	97	95	93	93	92	90	88			
2	102	96	90	85	100	94	88	84	90	86	82	87	83	80	84	81	79	77			
3	95	85	78	73	92	84	77	72	81	75	71	78	74	70	76	72	69	67			
4	87	77	69	63	85	75	68	63	73	67	62	71	65	61	69	64	60	58			
5	81	69	61	55	79	68	61	55	66	60	55	64	59	54	63	58	53	51			
6	75	63	55	49	73	62	54	49	60	54	49	59	53	48	57	52	48	46			
7	70	58	50	44	68	57	49	44	55	49	44	54	48	43	53	47	43	41			
8	65	53	45	40	64	52	45	40	51	44	39	50	44	39	49	43	39	37			
9	61	49	41	36	60	48	41	36	47	40	36	46	40	36	45	40	35	34			
10	58	45	38	33	56	45	38	33	44	37	33	43	37	33	42	37	33	31			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	59179
5°	58899
10°	57684
15°	55594
20°	53027
25°	50168
30°	47324
35°	44558
40°	41954
45°	39109
50°	35664
55°	31486
60°	26659
65°	20930
70°	14943
75°	8164
80°	1415
85°	0



TEST NUMBER: P839714

CATALOG NUMBER: LDS4C10D010 EU4109030 4LBSWH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	45.1	4.9
10°-20°	122.6	13.3
20°-30°	170.3	18.5
30°-40°	185.8	20.2
40°-50°	173.4	18.8
50°-60°	131.6	14.3
60°-70°	72.1	7.8
70°-80°	19.8	2.2
80°-90°	0.3	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	338.1	36.7
0°-40°	523.9	56.9
0°-60°	828.9	90.0
0°-90°	921.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	921.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	482	
5°	478	45
15°	437	123
25°	370	170
35°	297	186
45°	225	173
55°	147	132
65°	72	72
75°	17	20
85°	0	0
90°	0	



TEST NUMBER: P839714

CATALOG NUMBER: LDS4C10D010 EU4109030 4LBSWH

CANDELA DISTRIBUTION (FULL):

	0°
0°	481.7
2.5°	481.7
5°	477.6
7.5°	471.6
10°	462.4
12.5°	450.3
15°	437.1
17.5°	420.9
20°	405.6
22.5°	387.4
25°	370.1
27.5°	352.9
30°	333.6
32.5°	315.4
35°	297.1
37.5°	278.9
40°	261.6
42.5°	243.4
45°	225.1
47.5°	206.9
50°	186.6
52.5°	167.3
55°	147.0
57.5°	127.8
60°	108.5
62.5°	89.2
65°	72.0
67.5°	55.8
70°	41.6
72.5°	28.4
75°	17.2
77.5°	8.1
80°	2.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-50001EG





— 0°-180°







(END OF REPORT)