

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P839718

Luminaire Tested: **LDS4C10D010 EU4109035 4LBPSMB**

Issue Date: 8/24/2022



Test Information

Test Method: LM-79-08
Report Number: P839718
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2105-247-18)
Test Lab: INNOVATION CENTER
Issue Date: 8/24/2022
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LDS4C10D010 EU4109035 4LBPSMB
Description: 4 INCH 1000 LUMEN PORTFOLIO LED DOWNLIGHT WITH, 3500K, 90CRI LEDS
AND 4LBPS TRIM WITH MB FINISH
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 802.0 lumens
Efficiency: N/A
Efficacy: 81.8 lumens/watt
Spacing Criteria (0/90/45): 1.16 / 1.16 / 1.25
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 9.8
Input Voltage (V):
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P839718

CATALOG NUMBER: LDS4C10D010 EU4109035 4LBPSMB

Luminous Intensity Polar Plot





TEST NUMBER: P839718

CATALOG NUMBER: LDS4C10D010 EU4109035 4LBPSMB

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100	100	100	100
1	112	108	105	102	109	106	103	100	102	99	97	98	96	94	94	93	92	90	90	90	90
2	104	97	92	88	101	96	91	87	92	88	85	89	86	83	86	83	81	79	79	79	79
3	96	88	81	76	94	86	80	75	83	78	74	81	76	73	78	75	72	70	70	70	70
4	89	79	72	66	87	78	71	66	76	70	65	73	68	64	71	67	63	62	62	62	62
5	83	72	64	59	81	71	64	58	69	63	58	67	61	57	65	60	57	55	55	55	55
6	77	65	58	52	75	65	57	52	63	56	52	61	56	51	60	55	51	49	49	49	49
7	72	60	52	47	70	59	52	47	58	51	46	56	50	46	55	50	46	44	44	44	44
8	67	55	47	42	66	54	47	42	53	47	42	52	46	42	51	46	41	40	40	40	40
9	63	51	43	38	62	50	43	38	49	43	38	48	42	38	47	42	38	36	36	36	36
10	59	47	40	35	58	47	40	35	46	39	35	45	39	35	44	39	35	33	33	33	33

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	51734
5°	51561
10°	50997
15°	50112
20°	48988
25°	47688
30°	46175
35°	44408
40°	42162
45°	38327
50°	31650
55°	23304
60°	15824
65°	9273
70°	3664
75°	807
80°	1061
85°	1832



TEST NUMBER: P839718

CATALOG NUMBER: LDS4C10D010 EU4109035 4LBPSMB

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	39.6	4.9
10°-20°	110.9	13.8
20°-30°	161.8	20.2
30°-40°	184.7	23.0
40°-50°	167.9	20.9
50°-60°	99.0	12.4
60°-70°	33.2	4.1
70°-80°	3.4	0.4
80°-90°	1.2	0.2
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	312.4	39.0
0°-40°	497.1	62.0
0°-60°	764.1	95.3
0°-90°	802.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	802.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	421	
5°	418	40
15°	394	111
25°	352	162
35°	296	185
45°	221	168
55°	109	99
65°	32	33
75°	2	3
85°	1	1
90°	0	



TEST NUMBER: P839718

CATALOG NUMBER: LDS4C10D010 EU4109035 4LBPSMB

CANDELA DISTRIBUTION (FULL):

	0°
0°	421.1
2.5°	420.5
5°	418.1
7.5°	414.2
10°	408.8
12.5°	401.8
15°	394.0
17.5°	384.9
20°	374.7
22.5°	363.7
25°	351.8
27.5°	338.8
30°	325.5
32.5°	311.0
35°	296.1
37.5°	279.8
40°	262.9
42.5°	243.2
45°	220.6
47.5°	194.6
50°	165.6
52.5°	136.5
55°	108.8
57.5°	85.2
60°	64.4
62.5°	46.6
65°	31.9
67.5°	19.5
70°	10.2
72.5°	3.9
75°	1.7
77.5°	1.7
80°	1.5
82.5°	1.3
85°	1.3
87.5°	1.1
90°	0.0



Report Generated By 670246072 / DESKTOP-50001EG





— 0°-180°







(END OF REPORT)