

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P839738

Luminaire Tested: **LDS4C10D010 EU4109050 4LBPSMB**

Issue Date: 8/24/2022



Test Information

Test Method: LM-79-08
Report Number: P839738
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2105-247-18)
Test Lab: INNOVATION CENTER
Issue Date: 8/24/2022
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LDS4C10D010 EU4109050 4LBPSMB
Description: 4 INCH 1000 LUMEN PORTFOLIO LED DOWNLIGHT WITH, 5000K, 90CRI LEDS
AND 4LBPS TRIM WITH MB FINISH
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 820.0 lumens
Efficiency: N/A
Efficacy: 83.7 lumens/watt
Spacing Criteria (0/90/45): 1.16 / 1.16 / 1.25
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 9.8
Input Voltage (V):
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P839738

CATALOG NUMBER: LDS4C10D010 EU4109050 4LBPSMB

Luminous Intensity Polar Plot





TEST NUMBER: P839738

CATALOG NUMBER: LDS4C10D010 EU4109050 4LBPSMB

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			100
1	112	108	105	102	109	106	103	100	102	99	97	98	96	94	94	93	92	90			90
2	104	97	92	88	101	96	91	87	92	88	85	89	86	83	86	83	81	79			79
3	96	88	81	76	94	86	80	75	83	78	74	81	76	73	78	75	72	70			70
4	89	79	72	66	87	78	71	66	76	70	65	73	68	64	71	67	63	62			62
5	83	72	64	59	81	71	64	58	69	63	58	67	61	57	65	60	57	55			55
6	77	66	58	52	75	65	57	52	63	56	52	61	56	51	60	55	51	49			49
7	72	60	52	47	70	59	52	47	58	51	46	56	50	46	55	50	46	44			44
8	67	55	47	42	66	54	47	42	53	47	42	52	46	42	51	46	41	40			40
9	63	51	43	38	62	50	43	38	49	43	38	48	42	38	47	42	38	36			36
10	59	47	40	35	58	47	40	35	46	39	35	45	39	35	44	39	35	33			33

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	52901
5°	52720
10°	52132
15°	51244
20°	50086
25°	48759
30°	47211
35°	45398
40°	43108
45°	39196
50°	32358
55°	23818
60°	16168
65°	9477
70°	3736
75°	854
80°	1132
85°	1832



TEST NUMBER: P839738

CATALOG NUMBER: LDS4C10D010 EU4109050 4LBPSMB

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	40.5	4.9
10°-20°	113.4	13.8
20°-30°	165.5	20.2
30°-40°	188.9	23.0
40°-50°	171.7	20.9
50°-60°	101.3	12.3
60°-70°	33.9	4.1
70°-80°	3.6	0.4
80°-90°	1.2	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	319.4	39.0
0°-40°	508.3	62.0
0°-60°	781.2	95.3
0°-90°	820.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	820.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	431	
5°	428	41
15°	403	113
25°	360	165
35°	303	189
45°	226	172
55°	111	101
65°	33	34
75°	2	4
85°	1	1
90°	0	



TEST NUMBER: P839738

CATALOG NUMBER: LDS4C10D010 EU4109050 4LBPSMB

CANDELA DISTRIBUTION (FULL):

	0°
0°	430.6
2.5°	429.9
5°	427.5
7.5°	423.5
10°	417.9
12.5°	410.8
15°	402.9
17.5°	393.6
20°	383.1
22.5°	371.8
25°	359.7
27.5°	346.4
30°	332.8
32.5°	318.0
35°	302.7
37.5°	286.1
40°	268.8
42.5°	248.6
45°	225.6
47.5°	199.0
50°	169.3
52.5°	139.6
55°	111.2
57.5°	87.1
60°	65.8
62.5°	47.6
65°	32.6
67.5°	19.9
70°	10.4
72.5°	4.0
75°	1.8
77.5°	1.8
80°	1.6
82.5°	1.3
85°	1.3
87.5°	1.1
90°	0.0



Report Generated By 670246072 / DESKTOP-50001EG





— 0°-180°







(END OF REPORT)