

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P839869

Luminaire Tested: **LDS4C25D010 EU4259035 4LBPSMMS**

Issue Date: 8/24/2022



Test Information

Test Method: LM-79-08
Report Number: P839869
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2105-247-18)
Test Lab: INNOVATION CENTER
Issue Date: 8/24/2022
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LDS4C25D010 EU4259035 4LBPSMMS
Description: 4 INCH 2500 LUMEN PORTFOLIO LED DOWNLIGHT WITH, 3500K, 90CRI LEDS
AND 4LBPS TRIM WITH MMS FINISH
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 2037.0 lumens
Efficiency: N/A
Efficacy: 64.7 lumens/watt
Spacing Criteria (0/90/45): 1.16 / 1.16 / 1.25
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 31.5
Input Voltage (V):
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P839869

CATALOG NUMBER: LDS4C25D010 EU4259035 4LBPSMMS

Luminous Intensity Polar Plot





TEST NUMBER: P839869

CATALOG NUMBER: LDS4C25D010 EU4259035 4LBPSMMS

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100	100	100	100
1	112	108	105	102	109	106	103	100	102	99	97	98	96	94	94	93	92	90	90	90	90
2	104	97	92	88	101	96	91	87	92	88	85	89	86	83	86	83	81	79	79	79	79
3	96	88	81	76	94	86	80	75	83	78	74	81	76	73	78	75	72	70	70	70	70
4	89	79	72	66	87	78	71	66	76	70	65	73	68	64	71	67	63	62	62	62	62
5	83	72	64	59	81	71	64	58	69	63	58	67	61	57	65	60	57	55	55	55	55
6	77	65	58	52	75	65	57	52	63	56	52	61	56	51	60	55	51	49	49	49	49
7	72	60	52	47	70	59	52	47	58	51	46	56	50	46	55	50	46	44	44	44	44
8	67	55	47	42	66	54	47	42	53	47	42	52	46	42	51	46	41	40	40	40	40
9	63	51	43	38	62	50	43	38	49	43	38	48	42	38	47	42	38	36	36	36	36
10	59	47	40	35	58	47	40	35	46	39	35	45	39	35	44	39	35	33	33	33	33

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	131404
5°	130956
10°	129514
15°	127289
20°	124436
25°	121104
30°	117289
35°	112782
40°	107082
45°	97364
50°	80388
55°	59180
60°	40173
65°	23517
70°	9303
75°	2089
80°	2759
85°	4652



TEST NUMBER: P839869

CATALOG NUMBER: LDS4C25D010 EU4259035 4LBPSMMS

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	100.6	4.9
10°-20°	281.8	13.8
20°-30°	411.0	20.2
30°-40°	469.2	23.0
40°-50°	426.5	20.9
50°-60°	251.6	12.3
60°-70°	84.4	4.1
70°-80°	8.8	0.4
80°-90°	3.1	0.2
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	793.5	39.0
0°-40°	1262.6	62.0
0°-60°	1940.7	95.3
0°-90°	2037.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2037.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1070	
5°	1062	101
15°	1001	282
25°	893	411
35°	752	469
45°	560	427
55°	276	252
65°	81	84
75°	4	9
85°	3	3
90°	0	



TEST NUMBER: P839869

CATALOG NUMBER: LDS4C25D010 EU4259035 4LBPSMMS

CANDELA DISTRIBUTION (FULL):

	0°
0°	1069.6
2.5°	1067.9
5°	1061.9
7.5°	1052.0
10°	1038.2
12.5°	1020.6
15°	1000.8
17.5°	977.7
20°	951.8
22.5°	923.7
25°	893.4
27.5°	860.4
30°	826.8
32.5°	789.9
35°	752.0
37.5°	710.7
40°	667.7
42.5°	617.6
45°	560.4
47.5°	494.3
50°	420.6
52.5°	346.8
55°	276.3
57.5°	216.3
60°	163.5
62.5°	118.4
65°	80.9
67.5°	49.5
70°	25.9
72.5°	9.9
75°	4.4
77.5°	4.4
80°	3.9
82.5°	3.3
85°	3.3
87.5°	2.8
90°	0.0



Report Generated By 670246072 / DESKTOP-50001EG





— 0°-180°







(END OF REPORT)