

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P839943

Luminaire Tested: **LDS4C30D010 EU4309050 4LBSLI**

Issue Date: 8/24/2022

Test Information

Test Method: LM-79-08
Report Number: P839943
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P208407)
Test Lab: INNOVATION CENTER
Issue Date: 8/24/2022
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LDS4C30D010 EU4309050 4LBSLI
Description: 4 INCH 3000 LUMEN PORTFOLIO LED DOWNLIGHT WITH, 5000K, 90CRI LEDS
AND 4LBS TRIM WITH LI FINISH
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 3119.0 lumens
Efficiency: N/A
Efficacy: 98.7 lumens/watt
Spacing Criteria (0/90/45): 0.91 / 0.91 / 1
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 31.6
Input Voltage (V):
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P839943

CATALOG NUMBER: LDS4C30D010 EU4309050 4LBSLI

Luminous Intensity Polar Plot





TEST NUMBER: P839943

CATALOG NUMBER: LDS4C30D010 EU4309050 4LBSLI

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	112	108	105	102	109	106	103	101	102	100	98	98	96	95	95	93	92	90																			
2	104	98	93	88	102	96	91	87	93	89	85	90	86	84	87	84	82	80																			
3	97	89	82	77	95	87	81	77	84	79	75	82	78	74	79	76	73	71																			
4	90	81	73	68	88	79	73	68	77	71	67	75	70	66	73	69	65	63																			
5	84	73	66	61	82	72	65	60	70	64	60	69	63	59	67	62	59	57																			
6	79	67	60	54	77	66	59	54	65	58	54	63	58	53	62	57	53	51																			
7	74	62	54	49	72	61	54	49	60	53	49	58	53	48	57	52	48	46																			
8	69	57	50	45	68	57	50	45	55	49	45	54	49	44	53	48	44	42																			
9	65	53	46	41	64	53	46	41	52	45	41	51	45	41	50	44	41	39																			
10	61	50	43	38	60	49	42	38	48	42	38	47	42	38	46	41	37	36																			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	273607
5°	267401
10°	251119
15°	233630
20°	216685
25°	197515
30°	175848
35°	155870
40°	140087
45°	125389
50°	107566
55°	86532
60°	64474
65°	41163
70°	19828
75°	3275
80°	2405
85°	0



TEST NUMBER: P839943

CATALOG NUMBER: LDS4C30D010 EU4309050 4LBSLI

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	201.9	6.5
10°-20°	515.0	16.5
20°-30°	667.4	21.4
30°-40°	653.9	21.0
40°-50°	554.3	17.8
50°-60°	363.3	11.6
60°-70°	146.0	4.7
70°-80°	16.7	0.5
80°-90°	0.5	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1384.3	44.4
0°-40°	2038.2	65.3
0°-60°	2955.8	94.8
0°-90°	3119.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	3119.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2227	
5°	2168	202
15°	1837	515
25°	1457	667
35°	1039	654
45°	722	554
55°	404	363
65°	142	146
75°	7	17
85°	0	0
90°	0	



TEST NUMBER: P839943

CATALOG NUMBER: LDS4C30D010 EU4309050 4LBSLI

CANDELA DISTRIBUTION (FULL):

	0°
0°	2227.1
2.5°	2209.8
5°	2168.3
7.5°	2099.3
10°	2013.0
12.5°	1919.7
15°	1836.9
17.5°	1747.2
20°	1657.4
22.5°	1560.7
25°	1457.1
27.5°	1350.0
30°	1239.6
32.5°	1136.0
35°	1039.3
37.5°	959.9
40°	873.5
42.5°	797.6
45°	721.7
47.5°	642.2
50°	562.8
52.5°	483.4
55°	404.0
57.5°	331.5
60°	262.4
62.5°	200.2
65°	141.6
67.5°	93.2
70°	55.2
72.5°	24.1
75°	6.9
77.5°	3.4
80°	3.4
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-50001EG





— 0°-180°







(END OF REPORT)