

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P856857

Luminaire Tested: **LX4C10D010 EX4C109840 4LBWH**

Issue Date: 2/8/2022



Test Information

Test Method: LM-79-08
Report Number: P856857
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P206636)
Test Lab: INNOVATION CENTER
Issue Date: 2/8/2022
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LX4C10D010 EX4C109840 4LBWH
Description:
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 763.3 lumens
Efficiency: N/A
Efficacy: 77.9 lumens/watt
Spacing Criteria (0/90/45): 1.18 / 1.18 / 1.13
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 9.8
Input Voltage (V):
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P856857

CATALOG NUMBER: LX4C10D010 EX4C109840 4LBWH

Luminous Intensity Polar Plot





TEST NUMBER: P856857

CATALOG NUMBER: LX4C10D010 EX4C109840 4LBWH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	112	109	106	104	110	107	104	102	103	101	99	99	97	96	96	94	93	91			
2	105	100	95	91	103	98	93	90	95	91	88	91	88	86	89	86	84	82			
3	99	91	85	80	97	90	84	80	87	82	78	84	80	77	82	79	76	74			
4	92	83	77	72	90	82	76	71	80	75	70	78	73	70	76	72	69	67			
5	87	77	70	65	85	76	69	64	74	68	64	72	67	63	70	66	62	61			
6	81	71	64	58	80	70	63	58	68	62	58	67	61	57	65	61	57	55			
7	76	65	58	53	75	65	58	53	63	57	53	62	56	52	61	56	52	50			
8	72	60	53	49	70	60	53	49	59	53	48	58	52	48	57	52	48	46			
9	68	56	49	45	66	56	49	45	55	49	44	54	48	44	53	48	44	43			
10	64	52	46	41	63	52	46	41	51	45	41	50	45	41	49	44	41	39			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	60444
5°	60675
10°	60865
15°	60859
20°	60532
25°	59115
30°	55240
35°	47842
40°	37367
45°	26826
50°	17412
55°	10431
60°	6118
65°	3924
70°	2586
75°	1994
80°	1486
85°	0



TEST NUMBER: P856857

CATALOG NUMBER: LX4C10D010 EX4C109840 4LBWH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	46.9	6.1
10°-20°	135.0	17.7
20°-30°	199.2	26.1
30°-40°	196.6	25.8
40°-50°	120.3	15.8
50°-60°	46.1	6.0
60°-70°	14.4	1.9
70°-80°	4.2	0.6
80°-90°	0.6	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	381.1	49.9
0°-40°	577.7	75.7
0°-60°	744.1	97.5
0°-90°	763.3	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	763.3	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	492	
5°	492	47
15°	478	135
25°	436	199
35°	319	197
45°	154	120
55°	49	46
65°	14	14
75°	4	4
85°	0	1
90°	0	



TEST NUMBER: P856857

CATALOG NUMBER: LX4C10D010 EX4C109840 4LBWH

CANDELA DISTRIBUTION (FULL):

	0°
0°	492.0
2.5°	493.0
5°	492.0
7.5°	491.0
10°	487.9
12.5°	483.7
15°	478.5
17.5°	472.4
20°	463.0
22.5°	452.6
25°	436.1
27.5°	415.4
30°	389.4
32.5°	357.4
35°	319.0
37.5°	276.5
40°	233.0
42.5°	192.6
45°	154.4
47.5°	120.1
50°	91.1
52.5°	67.3
55°	48.7
57.5°	34.2
60°	24.9
62.5°	18.6
65°	13.5
67.5°	10.3
70°	7.2
72.5°	5.2
75°	4.2
77.5°	2.1
80°	2.1
82.5°	1.1
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-50001EG





— 0°-180°







(END OF REPORT)