

Scaled data based on original data using  
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State  
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P857166

Luminaire Tested: **LX4C20D010 EX4C209035 4LBMDLI**

Issue Date: 2/18/2022



**Test Information**

Test Method: LM-79-08  
Report Number: P857166  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2105-247-8)  
Test Lab: INNOVATION CENTER  
Issue Date: 2/18/2022  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: PORTFOLIO  
Catalog Number: LX4C20D010 EX4C209035 4LBMDLI  
Description: 4 INCH 2000 LUMEN PORTFOLIO LED DOWNLIGHT WITH, 3500K, 90CRI LEDS  
AND 4LRMD45 TRIM WITH LI FINISH  
Light Source: -  
Ballast/Driver: -


**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 1669.0 lumens  
Efficiency: N/A  
Efficacy: 76.6 lumens/watt  
Spacing Criteria (0/90/45): 0.84 / 0.84 / 0.82  
Luminous Opening: Circular (Dia: 0.33' x H: 0')  
CIE Type: Direct  
  
Input Watts (W): 21.8  
Input Voltage (V):  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT

TEST NUMBER: P857166

CATALOG NUMBER: LX4C20D010 EX4C209035 4LBMDLI

### Luminous Intensity Polar Plot





TEST NUMBER: P857166

CATALOG NUMBER: LX4C20D010 EX4C209035 4LBMDLI

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	114	111	109	107	111	109	107	105	105	103	102	101	100	99	98	97	96	94			
2	109	104	100	97	107	102	99	96	99	96	94	96	94	92	94	92	90	88			
3	104	98	93	89	102	96	92	89	94	90	87	91	88	86	89	87	85	83			
4	99	92	87	83	97	91	86	82	89	85	81	87	83	80	85	82	79	78			
5	94	87	81	77	93	86	81	77	84	79	76	82	78	75	81	77	75	73			
6	90	82	76	72	89	81	76	72	79	75	71	78	74	71	77	73	70	69			
7	86	77	72	68	85	77	71	68	75	71	67	74	70	67	73	69	67	65			
8	82	73	68	64	81	73	67	64	72	67	63	71	66	63	70	66	63	62			
9	79	70	64	60	78	69	64	60	68	63	60	67	63	60	66	63	60	58			
10	75	66	61	57	74	66	61	57	65	60	57	64	60	57	63	59	57	55			

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	269307
5°	278487
10°	281308
15°	253408
20°	210593
25°	165213
30°	120906
35°	62480
40°	29669
45°	10442
50°	2351
55°	1542
60°	1081
65°	814
70°	575
75°	380
80°	283
85°	0



TEST NUMBER: P857166

CATALOG NUMBER: LX4C20D010 EX4C209035 4LBMDLI

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	215.7	12.9
10°-20°	548.8	32.9
20°-30°	555.3	33.3
30°-40°	283.1	17.0
40°-50°	55.5	3.3
50°-60°	6.7	0.4
60°-70°	2.8	0.2
70°-80°	1.0	0.1
80°-90°	0.2	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1319.8	79.1
0°-40°	1602.8	96.0
0°-60°	1665.1	99.8
0°-90°	1669.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1669.0	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	2192	
5°	2258	216
15°	1992	549
25°	1219	555
35°	417	283
45°	60	55
55°	7	7
65°	3	3
75°	1	1
85°	0	0
90°	0	



TEST NUMBER: P857166

CATALOG NUMBER: LX4C20D010 EX4C209035 4LBMDLI

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	2192.1
2.5°	2212.4
5°	2258.2
7.5°	2284.4
10°	2255.0
12.5°	2155.9
15°	1992.4
17.5°	1799.4
20°	1610.8
22.5°	1415.4
25°	1218.8
27.5°	1023.0
30°	852.3
32.5°	642.2
35°	416.6
37.5°	278.9
40°	185.0
42.5°	116.2
45°	60.1
47.5°	21.5
50°	12.3
52.5°	9.2
55°	7.2
57.5°	5.6
60°	4.4
62.5°	3.6
65°	2.8
67.5°	2.0
70°	1.6
72.5°	1.2
75°	0.8
77.5°	0.8
80°	0.4
82.5°	0.4
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-50001EG







— 0°-180°







(END OF REPORT)