

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P857264

Luminaire Tested: **LX4C20D010 EX4C209835 4LBWLI**

Issue Date: 2/8/2022



Test Information

Test Method: LM-79-08
Report Number: P857264
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P208077)
Test Lab: INNOVATION CENTER
Issue Date: 2/8/2022
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LX4C20D010 EX4C209835 4LBWLI
Description:
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1783.6 lumens
Efficiency: N/A
Efficacy: 81.8 lumens/watt
Spacing Criteria (0/90/45): 1.29 / 1.29 / 1.18
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct

Input Watts (W): 21.8
Input Voltage (V):
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P857264

CATALOG NUMBER: LX4C20D010 EX4C209835 4LBWLI

Luminous Intensity Polar Plot





TEST NUMBER: P857264

CATALOG NUMBER: LX4C20D010 EX4C209835 4LBWLI

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100	100	100	100
1	113	110	107	105	110	108	105	103	104	102	100	100	98	97	96	95	94	92	92	92	92
2	106	101	97	93	104	99	95	92	96	93	90	93	90	88	90	88	86	84	84	84	84
3	100	93	87	83	98	92	86	82	89	85	81	86	83	80	84	81	78	77	77	77	77
4	94	86	79	75	92	84	79	74	82	77	73	80	76	72	78	75	72	70	70	70	70
5	88	79	72	68	87	78	72	67	76	71	67	74	70	66	73	69	65	64	64	64	64
6	83	73	66	62	82	72	66	61	71	65	61	69	64	60	68	63	60	58	58	58	58
7	78	68	61	56	77	67	61	56	66	60	56	64	59	55	63	59	55	54	54	54	54
8	74	63	56	52	72	62	56	51	61	55	51	60	55	51	59	54	51	49	49	49	49
9	69	59	52	48	68	58	52	47	57	51	47	56	51	47	55	50	47	45	45	45	45
10	66	55	48	44	65	54	48	44	53	48	44	53	47	44	52	47	43	42	42	42	42

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P857264

CATALOG NUMBER: LX4C20D010 EX4C209835 4LBWLI

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	106.9	6.0
10°-20°	337.2	18.9
20°-30°	526.1	29.5
30°-40°	511.9	28.7
40°-50°	255.7	14.3
50°-60°	39.6	2.2
60°-70°	4.8	0.3
70°-80°	1.4	0.1
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	970.2	54.4
0°-40°	1482.1	83.1
0°-60°	1777.4	99.7
0°-90°	1783.6	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1783.6	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1093	
5°	1107	107
15°	1191	337
25°	1156	526
35°	831	512
45°	321	256
55°	33	40
65°	4	5
75°	2	1
85°	0	0
90°	0	



TEST NUMBER: P857264

CATALOG NUMBER: LX4C20D010 EX4C209835 4LBWLI

CANDELA DISTRIBUTION (FULL):

	0°
0°	1092.7
2.5°	1096.8
5°	1107.0
7.5°	1123.4
10°	1143.8
12.5°	1170.3
15°	1190.8
17.5°	1207.2
20°	1209.2
22.5°	1194.9
25°	1156.1
27.5°	1098.9
30°	1027.4
32.5°	937.6
35°	831.4
37.5°	714.8
40°	592.3
42.5°	461.7
45°	320.7
47.5°	206.3
50°	124.6
52.5°	67.4
55°	32.7
57.5°	14.4
60°	8.2
62.5°	6.2
65°	4.1
67.5°	4.1
70°	2.1
72.5°	2.1
75°	2.1
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-50001EG





— 0°-180°







(END OF REPORT)