

Scaled data based on original data using  
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State  
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P857364

Luminaire Tested: **LX4C25D010 EX4C259030 4LBSH**

Issue Date: 2/14/2022



**Test Information**

Test Method: LM-79-08  
Report Number: P857364  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P205729)  
Test Lab: INNOVATION CENTER  
Issue Date: 2/14/2022  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: PORTFOLIO  
Catalog Number: LX4C25D010 EX4C259030 4LBSH  
Description: 4 INCH 2500 LUMEN PORTFOLIO LED DOWNLIGHT WITH, 3000K, 90CRI LEDS  
AND 4LBS TRIM WITH H FINISH  
Light Source: -  
Ballast/Driver: -


**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 2458.0 lumens  
Efficiency: N/A  
Efficacy: 78.0 lumens/watt  
Spacing Criteria (0/90/45): 1.06 / 1.06 / 1.17  
Luminous Opening: Circular (Dia: 0.33' x H: 0')  
CIE Type: Direct  
  
Input Watts (W): 31.5  
Input Voltage (V):  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT

TEST NUMBER: P857364

CATALOG NUMBER: LX4C25D010 EX4C259030 4LBSH

### Luminous Intensity Polar Plot





TEST NUMBER: P857364

CATALOG NUMBER: LX4C25D010 EX4C259030 4LBSH

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	111	107	104	101	108	105	102	99	101	98	96	97	95	93	93	92	90	88			
2	102	96	90	85	100	94	88	84	90	86	82	87	83	80	84	81	79	77			
3	95	85	78	73	92	84	77	72	81	75	71	78	74	70	76	72	69	67			
4	87	77	69	63	85	75	68	63	73	67	62	71	65	61	69	64	60	58			
5	81	69	61	55	79	68	61	55	66	60	55	64	59	54	63	58	53	51			
6	75	63	55	49	73	62	54	49	60	54	49	59	53	48	57	52	48	46			
7	70	58	50	44	68	57	49	44	55	49	44	54	48	43	53	47	43	41			
8	65	53	45	40	64	52	45	40	51	44	39	50	44	39	49	43	39	37			
9	61	49	41	36	60	48	41	36	47	40	36	46	40	36	45	40	35	34			
10	58	45	38	33	56	45	38	33	44	37	33	43	37	33	42	37	33	31			

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	157928
5°	157200
10°	153952
15°	148364
20°	141524
25°	133900
30°	126311
35°	118931
40°	111973
45°	104384
50°	95181
55°	84048
60°	71157
65°	55872
70°	39871
75°	21835
80°	3820
85°	0



TEST NUMBER: P857364

CATALOG NUMBER: LX4C25D010 EX4C259030 4LBSH

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	120.4	4.9
10°-20°	327.3	13.3
20°-30°	454.5	18.5
30°-40°	496.0	20.2
40°-50°	462.7	18.8
50°-60°	351.2	14.3
60°-70°	192.3	7.8
70°-80°	52.9	2.2
80°-90°	0.7	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	902.2	36.7
0°-40°	1398.2	56.9
0°-60°	2212.0	90.0
0°-90°	2458.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2458.0	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	1286	
5°	1275	120
15°	1166	327
25°	988	455
35°	793	496
45°	601	463
55°	392	351
65°	192	192
75°	46	53
85°	0	1
90°	0	



TEST NUMBER: P857364

CATALOG NUMBER: LX4C25D010 EX4C259030 4LBSH

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	1285.5
2.5°	1285.5
5°	1274.7
7.5°	1258.5
10°	1234.1
12.5°	1201.7
15°	1166.5
17.5°	1123.2
20°	1082.5
22.5°	1033.8
25°	987.8
27.5°	941.8
30°	890.4
32.5°	841.7
35°	793.0
37.5°	744.2
40°	698.2
42.5°	649.5
45°	600.8
47.5°	552.1
50°	498.0
52.5°	446.5
55°	392.4
57.5°	341.0
60°	289.6
62.5°	238.2
65°	192.2
67.5°	148.8
70°	111.0
72.5°	75.8
75°	46.0
77.5°	21.6
80°	5.4
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-50001EG







— 0°-180°







(END OF REPORT)