

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P857459

Luminaire Tested: **LX4C25D010 EX4C259830 4LBSH**

Issue Date: 2/14/2022



Test Information

Test Method: LM-79-08
Report Number: P857459
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P205729)
Test Lab: INNOVATION CENTER
Issue Date: 2/14/2022
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LX4C25D010 EX4C259830 4LBSH
Description:
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 2191.9 lumens
Efficiency: N/A
Efficacy: 69.6 lumens/watt
Spacing Criteria (0/90/45): 1.06 / 1.06 / 1.17
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 31.5
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P857459

CATALOG NUMBER: LX4C25D010 EX4C259830 4LBSH

Luminous Intensity Polar Plot





TEST NUMBER: P857459

CATALOG NUMBER: LX4C25D010 EX4C259830 4LBSH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	111	107	104	101	108	105	102	99	101	98	96	97	95	93	93	92	90	88			
2	102	96	90	85	100	94	88	84	90	86	82	87	83	80	84	81	79	77			
3	95	85	78	73	92	84	77	72	81	75	71	78	74	70	76	72	69	67			
4	87	77	69	63	85	75	68	63	73	67	62	71	65	61	69	64	60	58			
5	81	69	61	55	79	68	61	55	66	60	55	64	59	54	63	58	53	51			
6	75	63	55	49	73	62	54	49	60	54	49	59	53	48	57	52	48	46			
7	70	58	50	44	68	57	49	44	55	49	44	54	48	43	53	47	43	41			
8	65	53	45	40	64	52	45	40	51	44	39	50	44	39	49	43	39	37			
9	61	49	41	36	60	48	41	36	47	40	36	46	40	36	45	40	35	34			
10	58	45	38	33	56	45	38	33	44	37	33	43	37	33	42	37	33	31			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	140827
5°	140181
10°	137286
15°	132300
20°	126201
25°	119409
30°	112636
35°	106063
40°	99849
45°	93090
50°	84879
55°	74945
60°	63442
65°	49825
70°	35561
75°	19461
80°	3396
85°	0



TEST NUMBER: P857459

CATALOG NUMBER: LX4C25D010 EX4C259830 4LBSH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	107.4	4.9
10°-20°	291.9	13.3
20°-30°	405.3	18.5
30°-40°	442.3	20.2
40°-50°	412.6	18.8
50°-60°	313.2	14.3
60°-70°	171.5	7.8
70°-80°	47.2	2.2
80°-90°	0.7	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	804.5	36.7
0°-40°	1246.8	56.9
0°-60°	1972.6	90.0
0°-90°	2191.9	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2191.9	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1146	
5°	1137	107
15°	1040	292
25°	881	405
35°	707	442
45°	536	413
55°	350	313
65°	171	171
75°	41	47
85°	0	1
90°	0	



TEST NUMBER: P857459

CATALOG NUMBER: LX4C25D010 EX4C259830 4LBSH

CANDELA DISTRIBUTION (FULL):

	0°
0°	1146.3
2.5°	1146.3
5°	1136.7
7.5°	1122.3
10°	1100.5
12.5°	1071.6
15°	1040.2
17.5°	1001.6
20°	965.3
22.5°	921.9
25°	880.9
27.5°	839.8
30°	794.0
32.5°	750.6
35°	707.2
37.5°	663.6
40°	622.6
42.5°	579.2
45°	535.8
47.5°	492.3
50°	444.1
52.5°	398.2
55°	349.9
57.5°	304.1
60°	258.2
62.5°	212.4
65°	171.4
67.5°	132.7
70°	99.0
72.5°	67.6
75°	41.0
77.5°	19.3
80°	4.8
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-50001EG





— 0°-180°







(END OF REPORT)