

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P858104

Luminaire Tested: **LD4C45D010 EU4459027 4LBMLI**

Issue Date: 7/19/2024

Test Information

Test Method: LM-79-08
Report Number: P858104
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P208178)
Test Lab: INNOVATION CENTER
Issue Date: 7/19/2024
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LD4C45D010 EU4459027 4LBMLI
Description: 4 INCH 4500 LUMEN PORTFOLIO LED DOWNLIGHT WITH, 2700K, 90CRI LEDS
AND 4LBM TRIM WITH LI FINISH
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 4204.1 lumens
Efficiency: N/A
Efficacy: 84.8 lumens/watt
Spacing Criteria (0/90/45): 0.7 / 0.7 / 0.76
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 49.6
Input Voltage (V):
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P858104

CATALOG NUMBER: LD4C45D010 EU4459027 4LBMLI

Luminous Intensity Polar Plot





TEST NUMBER: P858104

CATALOG NUMBER: LD4C45D010 EU4459027 4LBMLI

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	114	111	109	107	111	109	107	105	105	103	102	101	100	99	98	97	96	94			
2	109	104	100	97	107	102	99	96	99	96	94	96	94	92	94	92	90	88			
3	104	98	93	89	102	96	92	89	94	90	87	91	88	86	89	87	85	83			
4	99	92	87	83	97	91	86	82	89	85	81	87	83	80	85	82	79	78			
5	94	87	81	77	93	86	81	77	84	79	76	82	78	75	81	77	75	73			
6	90	82	76	72	89	81	76	72	80	75	71	78	74	71	77	73	71	69			
7	86	77	72	68	85	77	71	68	75	71	67	74	70	67	73	69	67	65			
8	82	73	68	64	81	73	67	64	72	67	64	71	66	63	70	66	63	62			
9	79	70	64	60	78	69	64	60	68	63	60	67	63	60	67	63	60	58			
10	75	66	61	57	74	66	61	57	65	60	57	64	60	57	64	60	57	56			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	814187
5°	800352
10°	735394
15°	615854
20°	493405
25°	396441
30°	295123
35°	168588
40°	79128
45°	33602
50°	10703
55°	5440
60°	3759
65°	2965
70°	1832
75°	0
80°	0
85°	0



TEST NUMBER: P858104

CATALOG NUMBER: LD4C45D010 EU4459027 4LBMLI

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	600.1	14.3
10°-20°	1341.5	31.9
20°-30°	1333.8	31.7
30°-40°	726.3	17.3
40°-50°	167.9	4.0
50°-60°	23.6	0.6
60°-70°	8.8	0.2
70°-80°	2.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	3275.4	77.9
0°-40°	4001.7	95.2
0°-60°	4193.3	99.7
0°-90°	4204.1	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	4204.1	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	6627	
5°	6490	600
15°	4842	1342
25°	2925	1334
35°	1124	726
45°	193	168
55°	25	24
65°	10	9
75°	0	2
85°	0	0
90°	0	



TEST NUMBER: P858104

CATALOG NUMBER: LD4C45D010 EU4459027 4LBMLI

CANDELA DISTRIBUTION (FULL):

	0°
0°	6627.3
2.5°	6612.1
5°	6489.9
7.5°	6240.8
10°	5895.0
12.5°	5386.4
15°	4842.1
17.5°	4303.0
20°	3774.0
22.5°	3341.7
25°	2924.6
27.5°	2527.9
30°	2080.4
32.5°	1581.9
35°	1124.1
37.5°	757.8
40°	493.4
42.5°	310.2
45°	193.4
47.5°	112.0
50°	56.0
52.5°	30.5
55°	25.4
57.5°	15.3
60°	15.3
62.5°	10.2
65°	10.2
67.5°	5.1
70°	5.1
72.5°	5.1
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-50001EG





— 0°-180°







(END OF REPORT)