

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P858137

Luminaire Tested: **LX4C45D010 EX4C459030 4LBWLI**

Issue Date: 2/8/2022



Test Information

Test Method: LM-79-08
Report Number: P858137
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P208077)
Test Lab: INNOVATION CENTER
Issue Date: 2/8/2022
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LX4C45D010 EX4C459030 4LBWLI
Description: 4 INCH 4500 LUMEN PORTFOLIO LED DOWNLIGHT WITH, 3000K, 90CRI LEDS
AND 4LBW TRIM WITH LI FINISH
Light Source: -
Ballast/Driver:


Summary

Lumens per Lamp: N/A
Luminaire Lumens: 4613.0 lumens
Efficiency: N/A
Efficacy: 93.0 lumens/watt
Spacing Criteria (0/90/45): 1.29 / 1.29 / 1.18
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct

Input Watts (W): 49.6
Input Voltage (V):
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P858137
CATALOG NUMBER: LX4C45D010 EX4C459030 4LBWLI

Luminous Intensity Polar Plot





TEST NUMBER: P858137

CATALOG NUMBER: LX4C45D010 EX4C459030 4LBWLI

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100	100	100	100
1	113	110	107	105	110	108	105	103	104	102	100	100	98	97	96	95	94	92	92	92	92
2	106	101	97	93	104	99	95	92	96	93	90	93	90	88	90	88	86	84	84	84	84
3	100	93	87	83	98	92	86	82	89	85	81	86	83	80	84	81	78	77	77	77	77
4	94	86	79	75	92	84	79	74	82	77	73	80	76	72	78	75	72	70	70	70	70
5	88	79	72	68	87	78	72	67	76	71	67	74	70	66	73	69	65	64	64	64	64
6	83	73	66	62	82	72	66	61	71	65	61	69	64	60	68	63	60	58	58	58	58
7	78	68	61	56	77	67	61	56	66	60	56	64	59	55	63	59	55	54	54	54	54
8	74	63	56	52	72	62	56	51	61	55	51	60	55	51	59	54	51	49	49	49	49
9	69	59	52	48	68	58	52	47	57	51	47	56	51	47	55	50	47	45	45	45	45
10	66	55	48	44	65	54	48	44	53	48	44	53	47	44	52	47	43	42	42	42	42

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P858137

CATALOG NUMBER: LX4C45D010 EX4C459030 4LBWLI

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	276.4	6.0
10°-20°	872.3	18.9
20°-30°	1360.7	29.5
30°-40°	1324.0	28.7
40°-50°	661.3	14.3
50°-60°	102.4	2.2
60°-70°	12.4	0.3
70°-80°	3.5	0.1
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2509.4	54.4
0°-40°	3833.4	83.1
0°-60°	4597.1	99.7
0°-90°	4613.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	4613.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2826	
5°	2863	276
15°	3080	872
25°	2990	1361
35°	2150	1324
45°	830	661
55°	85	102
65°	11	12
75°	5	3
85°	0	0
90°	0	



TEST NUMBER: P858137

CATALOG NUMBER: LX4C45D010 EX4C459030 4LBWLI

CANDELA DISTRIBUTION (FULL):

	0°
0°	2826.4
2.5°	2836.9
5°	2863.4
7.5°	2905.7
10°	2958.6
12.5°	3027.1
15°	3080.0
17.5°	3122.3
20°	3127.6
22.5°	3090.6
25°	2990.3
27.5°	2842.2
30°	2657.3
32.5°	2425.1
35°	2150.2
37.5°	1849.0
40°	1532.1
42.5°	1194.0
45°	829.5
47.5°	533.5
50°	322.2
52.5°	174.3
55°	84.6
57.5°	37.0
60°	21.2
62.5°	15.9
65°	10.6
67.5°	10.6
70°	5.3
72.5°	5.3
75°	5.3
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-50001EG





— 0°-180°







(END OF REPORT)