

Scaled data based on original data using  
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State  
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P858173

Luminaire Tested: **LX4C45D010 EX4C459040 4LBNH**

Issue Date: 2/8/2022



**Test Information**

Test Method: LM-79-08  
Report Number: P858173  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P207666)  
Test Lab: INNOVATION CENTER  
Issue Date: 2/8/2022  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: PORTFOLIO  
Catalog Number: LX4C45D010 EX4C459040 4LBNH  
Description: 4 INCH 4500 LUMEN PORTFOLIO LED DOWNLIGHT WITH, 4000K, 90CRI LEDS  
AND 4LBN TRIM WITH H FINISH  
Light Source: -  
Ballast/Driver:


**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 2957.0 lumens  
Efficiency: N/A  
Efficacy: 59.6 lumens/watt  
Spacing Criteria (0/90/45): 0.81 / 0.81 / 0.85  
Luminous Opening: Circular (Dia: 0.33' x H: 0')  
CIE Type: Direct  
  
Input Watts (W): 49.6  
Input Voltage (V):  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT

TEST NUMBER: P858173

CATALOG NUMBER: LX4C45D010 EX4C459040 4LBNH

### Luminous Intensity Polar Plot





TEST NUMBER: P858173

CATALOG NUMBER: LX4C45D010 EX4C459040 4LBNH

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	113	111	108	106	111	109	106	104	105	103	101	101	99	98	97	96	95	93			
2	108	103	99	96	106	101	98	94	98	95	92	95	93	90	92	90	89	87			
3	102	96	91	87	100	95	90	86	92	88	85	90	86	84	87	85	82	81			
4	97	90	84	80	95	89	83	79	86	82	78	84	81	78	83	79	77	75			
5	92	84	78	74	91	83	78	73	81	76	73	80	75	72	78	74	72	70			
6	88	79	73	69	86	78	72	68	77	72	68	75	71	67	74	70	67	65			
7	83	74	68	64	82	73	68	64	72	67	63	71	66	63	70	66	63	61			
8	79	70	64	60	78	69	64	60	68	63	59	67	63	59	66	62	59	58			
9	76	66	60	56	74	65	60	56	65	59	56	64	59	56	63	59	55	54			
10	72	62	57	53	71	62	56	53	61	56	53	60	56	52	60	55	52	51			

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	456106
5°	445960
10°	412332
15°	369988
20°	325694
25°	280298
30°	225712
35°	150261
40°	78166
45°	35391
50°	15347
55°	10302
60°	6610
65°	4680
70°	3843
75°	2563
80°	0
85°	0



TEST NUMBER: P858173

CATALOG NUMBER: LX4C45D010 EX4C459040 4LBNH

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	335.0	11.3
10°-20°	812.5	27.5
20°-30°	943.3	31.9
30°-40°	624.7	21.1
40°-50°	175.2	5.9
50°-60°	44.0	1.5
60°-70°	16.5	0.6
70°-80°	5.7	0.2
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2090.8	70.7
0°-40°	2715.5	91.8
0°-60°	2934.8	99.2
0°-90°	2957.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2957.0	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	3713	
5°	3616	335
15°	2909	813
25°	2068	943
35°	1002	625
45°	204	175
55°	48	44
65°	16	17
75°	5	6
85°	0	0
90°	0	



TEST NUMBER: P858173

CATALOG NUMBER: LX4C45D010 EX4C459040 4LBNH

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	3712.6
2.5°	3696.5
5°	3616.2
7.5°	3476.8
10°	3305.3
12.5°	3112.4
15°	2909.0
17.5°	2710.7
20°	2491.2
22.5°	2287.6
25°	2067.8
27.5°	1859.0
30°	1591.1
32.5°	1307.1
35°	1001.9
37.5°	717.9
40°	487.4
42.5°	316.0
45°	203.7
47.5°	123.3
50°	80.3
52.5°	58.8
55°	48.1
57.5°	37.6
60°	26.9
62.5°	21.5
65°	16.1
67.5°	10.7
70°	10.7
72.5°	5.4
75°	5.4
77.5°	5.4
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-50001EG







— 0°-180°







(END OF REPORT)