

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P858228

Luminaire Tested: **LX4C45D010 EX4C459830 4LBSLI**

Issue Date: 2/9/2022



Test Information

Test Method: LM-79-08
Report Number: P858228
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P208407)
Test Lab: INNOVATION CENTER
Issue Date: 2/9/2022
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LX4C45D010 EX4C459830 4LBSLI
Description:
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 4256.2 lumens
Efficiency: N/A
Efficacy: 85.8 lumens/watt
Spacing Criteria (0/90/45): 0.91 / 0.91 / 1
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 49.6
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P858228

CATALOG NUMBER: LX4C45D010 EX4C459830 4LBSLI

Luminous Intensity Polar Plot





TEST NUMBER: P858228

CATALOG NUMBER: LX4C45D010 EX4C459830 4LBSLI

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			100
1	112	108	105	102	109	106	103	101	102	100	98	98	96	95	95	93	92	90			90
2	104	98	93	88	102	96	91	87	93	89	85	90	86	84	87	84	82	80			80
3	97	89	82	77	95	87	81	77	84	79	75	82	78	74	79	76	73	71			71
4	90	81	73	68	88	79	73	68	77	71	67	75	70	66	73	69	65	63			63
5	84	73	66	61	82	72	65	60	70	64	60	69	63	59	67	62	59	57			57
6	79	67	60	54	77	66	59	54	65	58	54	63	58	53	62	57	53	51			51
7	74	62	54	49	72	61	54	49	60	53	49	58	53	48	57	52	48	46			46
8	69	57	50	45	68	57	50	45	55	49	45	54	49	44	53	48	44	42			42
9	65	53	46	41	64	53	46	41	52	45	41	51	45	41	50	44	41	39			39
10	61	50	43	38	60	49	42	38	48	42	38	47	42	38	46	41	37	36			36

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	373364
5°	364912
10°	342672
15°	318820
20°	295677
25°	269535
30°	239954
35°	212697
40°	191182
45°	171100
50°	146785
55°	118082
60°	87963
65°	56162
70°	27084
75°	4509
80°	3254
85°	0



TEST NUMBER: P858228

CATALOG NUMBER: LX4C45D010 EX4C459830 4LBSLI

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	275.6	6.5
10°-20°	702.8	16.5
20°-30°	910.7	21.4
30°-40°	892.3	21.0
40°-50°	756.4	17.8
50°-60°	495.8	11.6
60°-70°	199.3	4.7
70°-80°	22.8	0.5
80°-90°	0.6	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1889.1	44.4
0°-40°	2781.4	65.3
0°-60°	4033.6	94.8
0°-90°	4256.2	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	4256.2	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	3039	
5°	2959	276
15°	2507	703
25°	1988	911
35°	1418	892
45°	985	756
55°	551	496
65°	193	199
75°	10	23
85°	0	1
90°	0	



TEST NUMBER: P858228

CATALOG NUMBER: LX4C45D010 EX4C459830 4LBSLI

CANDELA DISTRIBUTION (FULL):

	0°
0°	3039.1
2.5°	3015.5
5°	2959.0
7.5°	2864.7
10°	2746.9
12.5°	2619.8
15°	2506.7
17.5°	2384.3
20°	2261.6
22.5°	2129.7
25°	1988.4
27.5°	1842.2
30°	1691.5
32.5°	1550.2
35°	1418.2
37.5°	1310.0
40°	1192.1
42.5°	1088.5
45°	984.8
47.5°	876.4
50°	768.0
52.5°	659.7
55°	551.3
57.5°	452.3
60°	358.0
62.5°	273.2
65°	193.2
67.5°	127.3
70°	75.4
72.5°	32.9
75°	9.5
77.5°	4.6
80°	4.6
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-50001EG





— 0°-180°







(END OF REPORT)