

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P858262

Luminaire Tested: **LX4C45D010 EX4C459850 4LBMH**

Issue Date: 2/8/2022



Test Information

Test Method: LM-79-08
Report Number: P858262
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P206636)
Test Lab: INNOVATION CENTER
Issue Date: 2/8/2022
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LX4C45D010 EX4C459850 4LBMH
Description:
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 3237.9 lumens
Efficiency: N/A
Efficacy: 65.3 lumens/watt
Spacing Criteria (0/90/45): 1.18 / 1.18 / 1.13
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 49.6
Input Voltage (V):
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P858262

CATALOG NUMBER: LX4C45D010 EX4C459850 4LBMH

Luminous Intensity Polar Plot





TEST NUMBER: P858262

CATALOG NUMBER: LX4C45D010 EX4C459850 4LBMH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

| | | | | | | | | | | | | | | | | | | | | | |
|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|----|-----|
| RF | 20 | | | | 20 | | | | 20 | | | | 20 | | | | 20 | | | | |
| RC | 80 | | | | 70 | | | | 50 | | | | 30 | | | | 10 | | | 0 | |
| RW | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 0 |
| RCR | | | | | | | | | | | | | | | | | | | | | |
| 0 | 119 | 119 | 119 | 119 | 116 | 116 | 116 | 116 | 111 | 111 | 111 | 106 | 106 | 106 | 102 | 102 | 102 | 100 | | | 100 |
| 1 | 112 | 109 | 106 | 104 | 110 | 107 | 104 | 102 | 103 | 101 | 99 | 99 | 97 | 96 | 96 | 94 | 93 | 91 | | | 91 |
| 2 | 105 | 100 | 95 | 91 | 103 | 98 | 93 | 90 | 95 | 91 | 88 | 91 | 88 | 86 | 89 | 86 | 84 | 82 | | | 82 |
| 3 | 99 | 91 | 85 | 80 | 97 | 90 | 84 | 80 | 87 | 82 | 78 | 84 | 80 | 77 | 82 | 79 | 76 | 74 | | | 74 |
| 4 | 92 | 83 | 77 | 72 | 90 | 82 | 76 | 71 | 80 | 75 | 70 | 78 | 73 | 70 | 76 | 72 | 69 | 67 | | | 67 |
| 5 | 87 | 77 | 70 | 65 | 85 | 76 | 69 | 64 | 74 | 68 | 64 | 72 | 67 | 63 | 70 | 66 | 62 | 61 | | | 61 |
| 6 | 81 | 71 | 64 | 58 | 80 | 70 | 63 | 58 | 68 | 62 | 58 | 67 | 61 | 57 | 65 | 61 | 57 | 55 | | | 55 |
| 7 | 76 | 65 | 58 | 53 | 75 | 65 | 58 | 53 | 63 | 57 | 53 | 62 | 56 | 52 | 61 | 56 | 52 | 50 | | | 50 |
| 8 | 72 | 60 | 53 | 49 | 70 | 60 | 53 | 49 | 59 | 53 | 48 | 58 | 52 | 48 | 57 | 52 | 48 | 46 | | | 46 |
| 9 | 68 | 56 | 49 | 45 | 66 | 56 | 49 | 45 | 55 | 49 | 44 | 54 | 48 | 44 | 53 | 48 | 44 | 43 | | | 43 |
| 10 | 64 | 52 | 46 | 41 | 63 | 52 | 46 | 41 | 51 | 45 | 41 | 50 | 45 | 41 | 49 | 44 | 41 | 39 | | | 39 |

AVERAGE LUMINANCE (cd/sqm):

| | |
|-----|--------|
| | 0° |
| 0° | 256395 |
| 5° | 257375 |
| 10° | 258167 |
| 15° | 258177 |
| 20° | 256756 |
| 25° | 250734 |
| 30° | 234351 |
| 35° | 202933 |
| 40° | 158530 |
| 45° | 113748 |
| 50° | 73908 |
| 55° | 44230 |
| 60° | 25873 |
| 65° | 16628 |
| 70° | 11063 |
| 75° | 8354 |
| 80° | 6226 |
| 85° | 0 |



TEST NUMBER: P858262

CATALOG NUMBER: LX4C45D010 EX4C459850 4LBMH

ZONAL LUMENS:

| Zone | Lumens | % Fixture |
|-----------|--------|-----------|
| 0°-10° | 198.7 | 6.1 |
| 10°-20° | 572.7 | 17.7 |
| 20°-30° | 845.1 | 26.1 |
| 30°-40° | 833.9 | 25.8 |
| 40°-50° | 510.3 | 15.8 |
| 50°-60° | 195.6 | 6.0 |
| 60°-70° | 61.2 | 1.9 |
| 70°-80° | 17.9 | 0.6 |
| 80°-90° | 2.4 | 0.1 |
| 90°-100° | 0.0 | 0.0 |
| 100°-110° | 0.0 | 0.0 |
| 110°-120° | 0.0 | 0.0 |
| 120°-130° | 0.0 | 0.0 |
| 130°-140° | 0.0 | 0.0 |
| 140°-150° | 0.0 | 0.0 |
| 150°-160° | 0.0 | 0.0 |
| 160°-170° | 0.0 | 0.0 |
| 170°-180° | 0.0 | 0.0 |
| 0°-30° | 1616.5 | 49.9 |
| 0°-40° | 2450.4 | 75.7 |
| 0°-60° | 3156.4 | 97.5 |
| 0°-90° | 3237.9 | 100.0 |
| 90°-120° | 0.0 | 0.0 |
| 90°-150° | 0.0 | 0.0 |
| 90°-180° | 0.0 | 0.0 |
| 0°-180° | 3237.9 | 100.0 |

CANDELA DISTRIBUTION:

| | 0° | Flux |
|-----|------|------|
| 0° | 2087 | |
| 5° | 2087 | 199 |
| 15° | 2030 | 573 |
| 25° | 1850 | 845 |
| 35° | 1353 | 834 |
| 45° | 655 | 510 |
| 55° | 206 | 196 |
| 65° | 57 | 61 |
| 75° | 18 | 18 |
| 85° | 0 | 2 |
| 90° | 0 | |



TEST NUMBER: P858262

CATALOG NUMBER: LX4C45D010 EX4C459850 4LBMH

CANDELA DISTRIBUTION (FULL):

| | 0° |
|-------|--------|
| 0° | 2087.0 |
| 2.5° | 2091.4 |
| 5° | 2087.0 |
| 7.5° | 2082.7 |
| 10° | 2069.5 |
| 12.5° | 2051.8 |
| 15° | 2029.9 |
| 17.5° | 2003.5 |
| 20° | 1963.9 |
| 22.5° | 1920.1 |
| 25° | 1849.7 |
| 27.5° | 1761.8 |
| 30° | 1652.0 |
| 32.5° | 1515.9 |
| 35° | 1353.1 |
| 37.5° | 1173.1 |
| 40° | 988.5 |
| 42.5° | 817.2 |
| 45° | 654.7 |
| 47.5° | 509.5 |
| 50° | 386.7 |
| 52.5° | 285.6 |
| 55° | 206.5 |
| 57.5° | 144.9 |
| 60° | 105.3 |
| 62.5° | 79.2 |
| 65° | 57.2 |
| 67.5° | 44.0 |
| 70° | 30.8 |
| 72.5° | 22.0 |
| 75° | 17.6 |
| 77.5° | 8.8 |
| 80° | 8.8 |
| 82.5° | 4.4 |
| 85° | 0.0 |
| 87.5° | 0.0 |
| 90° | 0.0 |



Report Generated By 670246072 / DESKTOP-50001EG





— 0°-180°







(END OF REPORT)