

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P858368

Luminaire Tested: **LD4C15W2N2050D010 4LBNH_2700K**

Issue Date: 11/9/2023



Test Information

Test Method: LM-79-08
Report Number: P858368
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P203666)
Test Lab: INNOVATION CENTER-P3
Issue Date: 11/9/2023
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LD4C15W2N2050D010 4LBNH_2700K
Description: 4 INCH 1500 LUMEN PORTFOLIO LED DOWNLIGHT WITH, 2700K, W2N2050 LEDS AND 4LBNH TRIM WITH FINISH

Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 810.1 lumens
Efficiency: N/A
Efficacy: 42.2 lumens/watt
Spacing Criteria (0/90/45): 0.78 / 0.78 / 0.84
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 19.2
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P858368

CATALOG NUMBER: LD4C15W2N2050D010 4LBNH_2700K

Luminous Intensity Polar Plot





TEST NUMBER: P858368

CATALOG NUMBER: LD4C15W2N2050D010 4LBNH_2700K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	113	111	108	106	111	109	106	104	104	103	101	101	99	98	97	96	95	93			
2	108	103	99	96	106	101	98	94	98	95	92	95	93	90	92	90	89	87			
3	102	96	91	87	100	95	90	86	92	88	85	90	86	84	87	85	82	81			
4	97	90	84	80	95	89	83	79	86	82	78	84	81	78	83	79	77	75			
5	92	84	78	74	91	83	78	73	81	76	73	80	75	72	78	74	72	70			
6	88	79	73	69	86	78	72	68	77	72	68	75	71	67	74	70	67	65			
7	83	74	68	64	82	73	68	64	72	67	63	71	66	63	70	66	63	61			
8	79	70	64	60	78	69	64	60	68	63	59	67	63	59	66	62	59	58			
9	76	66	60	56	75	66	60	56	65	59	56	64	59	56	63	59	55	54			
10	72	62	57	53	71	62	57	53	61	56	53	60	56	52	60	55	52	51			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	127559
5°	124408
10°	114794
15°	101635
20°	88248
25°	75476
30°	62234
35°	40974
40°	22035
45°	9747
50°	3956
55°	2849
60°	1818
65°	1308
70°	1078
75°	712
80°	1061
85°	0



TEST NUMBER: P858368

CATALOG NUMBER: LD4C15W2N2050D010 4LBNH_2700K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	93.4	11.5
10°-20°	222.7	27.5
20°-30°	255.1	31.5
30°-40°	171.4	21.2
40°-50°	49.0	6.0
50°-60°	12.0	1.5
60°-70°	4.6	0.6
70°-80°	1.8	0.2
80°-90°	0.2	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	571.1	70.5
0°-40°	742.5	91.7
0°-60°	803.5	99.2
0°-90°	810.1	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	810.1	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1038	
5°	1009	93
15°	799	223
25°	557	255
35°	273	171
45°	56	49
55°	13	12
65°	4	5
75°	2	2
85°	0	0
90°	0	



TEST NUMBER: P858368

CATALOG NUMBER: LD4C15W2N2050D010 4LBNH_2700K

CANDELA DISTRIBUTION (FULL):

	0°
0°	1038.3
2.5°	1031.0
5°	1008.8
7.5°	968.9
10°	920.2
12.5°	858.1
15°	799.1
17.5°	737.0
20°	675.0
22.5°	615.9
25°	556.8
27.5°	502.2
30°	438.7
32.5°	354.5
35°	273.2
37.5°	199.4
40°	137.4
42.5°	90.1
45°	56.1
47.5°	34.0
50°	20.7
52.5°	16.2
55°	13.3
57.5°	10.3
60°	7.4
62.5°	5.9
65°	4.5
67.5°	3.0
70°	3.0
72.5°	1.5
75°	1.5
77.5°	1.5
80°	1.5
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-50001EG





— 0°-180°







(END OF REPORT)