

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P858391

Luminaire Tested: **LD4C15W2N2050D010 4LBWLI_2000K**

Issue Date: 11/9/2023



Test Information

Test Method: LM-79-08
Report Number: P858391
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P208077)
Test Lab: INNOVATION CENTER-P3
Issue Date: 11/9/2023
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LD4C15W2N2050D010 4LBWLI_2000K
Description: 4 INCH 1500 LUMEN PORTFOLIO LED DOWNLIGHT WITH, 2000K, W2N2050 LEDS AND 4LBWLI TRIM WITH FINISH

Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1235.0 lumens
Efficiency: N/A
Efficacy: 64.3 lumens/watt
Spacing Criteria (0/90/45): 1.29 / 1.29 / 1.18
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 19.2
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P858391

CATALOG NUMBER: LD4C15W2N2050D010 4LBWLI_2000K

Luminous Intensity Polar Plot





TEST NUMBER: P858391

CATALOG NUMBER: LD4C15W2N2050D010 4LBWLI_2000K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100	100	100	100
1	113	110	107	105	110	108	105	103	104	102	100	100	98	97	96	95	94	92	92	92	92
2	106	101	97	93	104	99	95	92	96	93	90	93	90	88	90	88	86	84	84	84	84
3	100	93	87	83	98	92	86	82	89	85	81	86	83	80	84	81	78	77	77	77	77
4	94	86	79	75	92	84	79	74	82	77	73	80	76	72	78	75	72	70	70	70	70
5	88	79	72	68	87	78	72	67	76	71	67	74	70	66	73	69	65	64	64	64	64
6	83	73	66	62	82	72	66	61	71	65	61	69	64	60	68	63	60	58	58	58	58
7	78	68	61	56	77	67	61	56	66	60	56	64	59	55	63	59	55	54	54	54	54
8	74	63	56	52	72	62	56	51	61	55	51	60	55	51	59	54	51	49	49	49	49
9	69	59	52	48	68	58	52	47	57	51	47	56	51	47	55	50	47	45	45	45	45
10	66	55	48	44	65	54	48	44	53	48	44	53	47	44	52	47	43	42	42	42	42

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	92963
5°	94539
10°	98813
15°	104879
20°	109467
25°	108524
30°	100918
35°	86341
40°	65785
45°	38588
50°	16494
55°	4862
60°	1401
65°	814
70°	503
75°	665
80°	0
85°	0



TEST NUMBER: P858391

CATALOG NUMBER: LD4C15W2N2050D010 4LBWLI_2000K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	74.0	6.0
10°-20°	233.5	18.9
20°-30°	364.3	29.5
30°-40°	354.5	28.7
40°-50°	177.1	14.3
50°-60°	27.4	2.2
60°-70°	3.3	0.3
70°-80°	0.9	0.1
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	671.8	54.4
0°-40°	1026.3	83.1
0°-60°	1230.8	99.7
0°-90°	1235.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1235.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	757	
5°	767	74
15°	825	234
25°	801	364
35°	576	354
45°	222	177
55°	23	27
65°	3	3
75°	1	1
85°	0	0
90°	0	



TEST NUMBER: P858391

CATALOG NUMBER: LD4C15W2N2050D010 4LBWLI_2000K

CANDELA DISTRIBUTION (FULL):

0°	
0°	756.7
2.5°	759.5
5°	766.6
7.5°	777.9
10°	792.1
12.5°	810.4
15°	824.6
17.5°	835.9
20°	837.3
22.5°	827.4
25°	800.6
27.5°	760.9
30°	711.4
32.5°	649.2
35°	575.7
37.5°	495.0
40°	410.2
42.5°	319.7
45°	222.1
47.5°	142.8
50°	86.3
52.5°	46.7
55°	22.7
57.5°	9.9
60°	5.7
62.5°	4.2
65°	2.8
67.5°	2.8
70°	1.4
72.5°	1.4
75°	1.4
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-50001EG





— 0°-180°







(END OF REPORT)