

Scaled data based on original data using  
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State  
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P858436

Luminaire Tested: **LD4C15W2N2765D010 4LBWLI\_4000K**

Issue Date: 11/9/2023



**Test Information**

Test Method: LM-79-08  
Report Number: P858436  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P208077)  
Test Lab: INNOVATION CENTER-P3  
Issue Date: 11/9/2023  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: PORTFOLIO  
Catalog Number: LD4C15W2N2765D010 4LBWLI\_4000K  
Description: 4 INCH 1500 LUMEN PORTFOLIO LED DOWNLIGHT WITH, 4000K, W2N2765 LEDS AND 4LBWLI TRIM WITH FINISH  
  
Light Source: -  
Ballast/Driver: -

**Summary**


Lumens per Lamp: N/A  
Luminaire Lumens: 1426.0 lumens  
Efficiency: N/A  
Efficacy: 74.3 lumens/watt  
Spacing Criteria (0/90/45): 1.29 / 1.29 / 1.18  
Luminous Opening: Circular (Dia: 0.33' x H: 0')  
CIE Type: Direct

Input Watts (W): 19.2  
Input Voltage (V): NR  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT

TEST NUMBER: P858436

CATALOG NUMBER: LD4C15W2N2765D010 4LBWLI\_4000K

### Luminous Intensity Polar Plot





TEST NUMBER: P858436

CATALOG NUMBER: LD4C15W2N2765D010 4LBWLI\_4000K

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100	100	100	100
1	113	110	107	105	110	108	105	103	104	102	100	100	98	97	96	95	94	92	92	92	92
2	106	101	97	93	104	99	95	92	96	93	90	93	90	88	90	88	86	84	84	84	84
3	100	93	87	83	98	92	86	82	89	85	81	86	83	80	84	81	78	77	77	77	77
4	94	86	79	75	92	84	79	74	82	77	73	80	76	72	78	75	72	70	70	70	70
5	88	79	72	68	87	78	72	67	76	71	67	74	70	66	73	69	65	64	64	64	64
6	83	73	66	62	82	72	66	61	71	65	61	69	64	60	68	63	60	58	58	58	58
7	78	68	61	56	77	67	61	56	66	60	56	64	59	55	63	59	55	54	54	54	54
8	74	63	56	52	72	62	56	51	61	55	51	60	55	51	59	54	51	49	49	49	49
9	69	59	52	48	68	58	52	47	57	51	47	56	51	47	55	50	47	45	45	45	45
10	66	55	48	44	65	54	48	44	53	48	44	53	47	44	52	47	43	42	42	42	42

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	107337
5°	109153
10°	114095
15°	121095
20°	126397
25°	125306
30°	116537
35°	99689
40°	75953
45°	44547
50°	19036
55°	5612
60°	1597
65°	959
70°	575
75°	759
80°	0
85°	0



TEST NUMBER: P858436

CATALOG NUMBER: LD4C15W2N2765D010 4LBWLI\_4000K

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	85.4	6.0
10°-20°	269.6	18.9
20°-30°	420.6	29.5
30°-40°	409.3	28.7
40°-50°	204.4	14.3
50°-60°	31.6	2.2
60°-70°	3.8	0.3
70°-80°	1.0	0.1
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	775.7	54.4
0°-40°	1185.0	83.1
0°-60°	1421.1	99.7
0°-90°	1426.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1426.0	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	874	
5°	885	85
15°	952	270
25°	924	421
35°	665	409
45°	256	204
55°	26	32
65°	3	4
75°	2	1
85°	0	0
90°	0	



TEST NUMBER: P858436

CATALOG NUMBER: LD4C15W2N2765D010 4LBWLI\_4000K

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	873.7
2.5°	877.0
5°	885.1
7.5°	898.2
10°	914.6
12.5°	935.8
15°	952.1
17.5°	965.2
20°	966.8
22.5°	955.4
25°	924.4
27.5°	878.6
30°	821.5
32.5°	749.7
35°	664.7
37.5°	571.6
40°	473.6
42.5°	369.1
45°	256.4
47.5°	164.9
50°	99.6
52.5°	53.9
55°	26.2
57.5°	11.4
60°	6.5
62.5°	4.9
65°	3.3
67.5°	3.3
70°	1.6
72.5°	1.6
75°	1.6
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-50001EG







— 0°-180°







(END OF REPORT)