

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P858785

Luminaire Tested: **LX4C05D010 EX4C059027 4LBSH**

Issue Date: 2/14/2022

Test Information

Test Method: LM-79-08
Report Number: P858785
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P205729)
Test Lab: INNOVATION CENTER
Issue Date: 2/14/2022
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LX4C05D010 EX4C059027 4LBSH
Description: 4 INCH 500 LUMEN PORTFOLIO LED DOWNLIGHT WITH, 2700K, 90CRI LEDS AND 4LBS TRIM WITH H FINISH
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 618.0 lumens
Efficiency: N/A
Efficacy: 85.8 lumens/watt
Spacing Criteria (0/90/45): 1.06 / 1.06 / 1.17
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 7.2
Input Voltage (V):
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P858785

CATALOG NUMBER: LX4C05D010 EX4C059027 4LBSH

Luminous Intensity Polar Plot





TEST NUMBER: P858785

CATALOG NUMBER: LX4C05D010 EX4C059027 4LBSH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	111	107	104	101	108	105	102	99	101	98	96	97	95	93	93	92	90	88			
2	102	96	90	85	100	94	88	84	90	86	82	87	83	80	84	81	79	77			
3	95	85	78	73	92	84	77	72	81	75	71	78	74	70	76	72	69	67			
4	87	77	69	63	85	75	68	63	73	67	62	71	65	61	69	64	60	58			
5	81	69	61	55	79	68	61	55	66	60	55	64	59	54	63	58	53	51			
6	75	63	55	49	73	62	54	49	60	54	49	59	53	48	57	52	48	46			
7	70	58	50	44	68	57	49	44	55	49	44	54	48	43	53	47	43	41			
8	65	53	45	40	64	52	45	40	51	44	39	50	44	39	49	43	39	37			
9	61	49	41	36	60	48	41	36	47	40	36	46	40	36	45	40	35	34			
10	58	45	38	33	56	45	38	33	44	37	33	43	37	33	42	37	33	31			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	39706
5°	39525
10°	38710
15°	37304
20°	35587
25°	33672
30°	31762
35°	29905
40°	28146
45°	26252
50°	23929
55°	21140
60°	17887
65°	14041
70°	10022
75°	5506
80°	990
85°	0



TEST NUMBER: P858785

CATALOG NUMBER: LX4C05D010 EX4C059027 4LBSH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	30.3	4.9
10°-20°	82.3	13.3
20°-30°	114.3	18.5
30°-40°	124.7	20.2
40°-50°	116.3	18.8
50°-60°	88.3	14.3
60°-70°	48.3	7.8
70°-80°	13.3	2.2
80°-90°	0.2	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	226.8	36.7
0°-40°	351.5	56.9
0°-60°	556.2	90.0
0°-90°	618.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	618.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	323	
5°	320	30
15°	293	82
25°	248	114
35°	199	125
45°	151	116
55°	99	88
65°	48	48
75°	12	13
85°	0	0
90°	0	



TEST NUMBER: P858785

CATALOG NUMBER: LX4C05D010 EX4C059027 4LBSH

CANDELA DISTRIBUTION (FULL):

	0°
0°	323.2
2.5°	323.2
5°	320.5
7.5°	316.4
10°	310.3
12.5°	302.1
15°	293.3
17.5°	282.4
20°	272.2
22.5°	259.9
25°	248.4
27.5°	236.8
30°	223.9
32.5°	211.6
35°	199.4
37.5°	187.1
40°	175.5
42.5°	163.3
45°	151.1
47.5°	138.8
50°	125.2
52.5°	112.3
55°	98.7
57.5°	85.7
60°	72.8
62.5°	59.9
65°	48.3
67.5°	37.4
70°	27.9
72.5°	19.1
75°	11.6
77.5°	5.4
80°	1.4
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-50001EG





— 0°-180°







(END OF REPORT)