

Scaled data based on original data using  
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State  
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P858865

Luminaire Tested: **LX4C05D010 EX4C059827 4LBSLI**

Issue Date: 2/9/2022



**Test Information**

Test Method: LM-79-08  
Report Number: P858865  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P208407)  
Test Lab: INNOVATION CENTER  
Issue Date: 2/9/2022  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: PORTFOLIO  
Catalog Number: LX4C05D010 EX4C059827 4LBSLI  
Description:  
Light Source: -  
Ballast/Driver: -


**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 574.2 lumens  
Efficiency: N/A  
Efficacy: 79.8 lumens/watt  
Spacing Criteria (0/90/45): 0.91 / 0.91 / 1  
Luminous Opening: Circular (Dia: 0.33' x H: 0')  
CIE Type: Direct  
  
Input Watts (W): 7.2  
Input Voltage (V):  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT

TEST NUMBER: P858865

CATALOG NUMBER: LX4C05D010 EX4C059827 4LBSLI

### Luminous Intensity Polar Plot





TEST NUMBER: P858865

CATALOG NUMBER: LX4C05D010 EX4C059827 4LBSLI

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

|     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |    |    |   |
|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|----|---|
| RF  | 20  |     |     |     | 20  |     |     |     | 20  |     |     |     | 20  |     |     |     | 20  |     |    |    |   |
| RC  | 80  |     |     |     | 70  |     |     |     | 50  |     |     |     | 30  |     |     |     | 10  |     |    | 0  |   |
| RW  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 50  | 30  | 10  | 50  | 30  | 10  | 50  | 30  | 10  | 50  | 30 | 10 | 0 |
| RCR |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |    |    |   |
| 0   | 119 | 119 | 119 | 119 | 116 | 116 | 116 | 116 | 111 | 111 | 111 | 106 | 106 | 106 | 102 | 102 | 102 | 100 |    |    |   |
| 1   | 112 | 108 | 105 | 102 | 109 | 106 | 103 | 101 | 102 | 100 | 98  | 98  | 96  | 95  | 95  | 93  | 92  | 90  |    |    |   |
| 2   | 104 | 98  | 93  | 88  | 102 | 96  | 91  | 87  | 93  | 89  | 85  | 90  | 86  | 84  | 87  | 84  | 82  | 80  |    |    |   |
| 3   | 97  | 89  | 82  | 77  | 95  | 87  | 81  | 77  | 84  | 79  | 75  | 82  | 78  | 74  | 79  | 76  | 73  | 71  |    |    |   |
| 4   | 90  | 81  | 73  | 68  | 88  | 79  | 73  | 68  | 77  | 71  | 67  | 75  | 70  | 66  | 73  | 69  | 65  | 63  |    |    |   |
| 5   | 84  | 73  | 66  | 61  | 82  | 72  | 65  | 60  | 70  | 64  | 60  | 69  | 63  | 59  | 67  | 62  | 59  | 57  |    |    |   |
| 6   | 79  | 67  | 60  | 54  | 77  | 66  | 59  | 54  | 65  | 58  | 54  | 63  | 58  | 53  | 62  | 57  | 53  | 51  |    |    |   |
| 7   | 74  | 62  | 54  | 49  | 72  | 61  | 54  | 49  | 60  | 53  | 49  | 58  | 53  | 48  | 57  | 52  | 48  | 46  |    |    |   |
| 8   | 69  | 57  | 50  | 45  | 68  | 57  | 50  | 45  | 55  | 49  | 45  | 54  | 49  | 44  | 53  | 48  | 44  | 42  |    |    |   |
| 9   | 65  | 53  | 46  | 41  | 64  | 53  | 46  | 41  | 52  | 45  | 41  | 51  | 45  | 41  | 50  | 44  | 41  | 39  |    |    |   |
| 10  | 61  | 50  | 43  | 38  | 60  | 49  | 42  | 38  | 48  | 42  | 38  | 47  | 42  | 38  | 46  | 41  | 37  | 36  |    |    |   |

**AVERAGE LUMINANCE (cd/sqm):**

|     |       |
|-----|-------|
|     | 0°    |
| 0°  | 50370 |
| 5°  | 49230 |
| 10° | 46232 |
| 15° | 43015 |
| 20° | 39901 |
| 25° | 36369 |
| 30° | 32372 |
| 35° | 28705 |
| 40° | 25804 |
| 45° | 23090 |
| 50° | 19801 |
| 55° | 15936 |
| 60° | 11868 |
| 65° | 7558  |
| 70° | 3664  |
| 75° | 570   |
| 80° | 424   |
| 85° | 0     |



TEST NUMBER: P858865

CATALOG NUMBER: LX4C05D010 EX4C059827 4LBSLI

**ZONAL LUMENS:**

| Zone      | Lumens | % Fixture |
|-----------|--------|-----------|
| 0°-10°    | 37.2   | 6.5       |
| 10°-20°   | 94.8   | 16.5      |
| 20°-30°   | 122.9  | 21.4      |
| 30°-40°   | 120.4  | 21.0      |
| 40°-50°   | 102.1  | 17.8      |
| 50°-60°   | 66.9   | 11.6      |
| 60°-70°   | 26.8   | 4.7       |
| 70°-80°   | 3.1    | 0.5       |
| 80°-90°   | 0.1    | 0.0       |
| 90°-100°  | 0.0    | 0.0       |
| 100°-110° | 0.0    | 0.0       |
| 110°-120° | 0.0    | 0.0       |
| 120°-130° | 0.0    | 0.0       |
| 130°-140° | 0.0    | 0.0       |
| 140°-150° | 0.0    | 0.0       |
| 150°-160° | 0.0    | 0.0       |
| 160°-170° | 0.0    | 0.0       |
| 170°-180° | 0.0    | 0.0       |
| 0°-30°    | 254.9  | 44.4      |
| 0°-40°    | 375.3  | 65.4      |
| 0°-60°    | 544.2  | 94.8      |
| 0°-90°    | 574.2  | 100.0     |
| 90°-120°  | 0.0    | 0.0       |
| 90°-150°  | 0.0    | 0.0       |
| 90°-180°  | 0.0    | 0.0       |
| 0°-180°   | 574.2  | 100.0     |

**CANDELA DISTRIBUTION:**

|     | 0°  | Flux |
|-----|-----|------|
| 0°  | 410 |      |
| 5°  | 399 | 37   |
| 15° | 338 | 95   |
| 25° | 268 | 123  |
| 35° | 191 | 120  |
| 45° | 133 | 102  |
| 55° | 74  | 67   |
| 65° | 26  | 27   |
| 75° | 1   | 3    |
| 85° | 0   | 0    |
| 90° | 0   |      |



TEST NUMBER: P858865

CATALOG NUMBER: LX4C05D010 EX4C059827 4LBSLI

**CANDELA DISTRIBUTION (FULL):**

|       | 0°    |
|-------|-------|
| 0°    | 410.0 |
| 2.5°  | 406.9 |
| 5°    | 399.2 |
| 7.5°  | 386.5 |
| 10°   | 370.6 |
| 12.5° | 353.5 |
| 15°   | 338.2 |
| 17.5° | 321.7 |
| 20°   | 305.2 |
| 22.5° | 287.3 |
| 25°   | 268.3 |
| 27.5° | 248.5 |
| 30°   | 228.2 |
| 32.5° | 209.2 |
| 35°   | 191.4 |
| 37.5° | 176.7 |
| 40°   | 160.9 |
| 42.5° | 146.9 |
| 45°   | 132.9 |
| 47.5° | 118.2 |
| 50°   | 103.6 |
| 52.5° | 89.0  |
| 55°   | 74.4  |
| 57.5° | 61.0  |
| 60°   | 48.3  |
| 62.5° | 36.8  |
| 65°   | 26.0  |
| 67.5° | 17.1  |
| 70°   | 10.2  |
| 72.5° | 4.5   |
| 75°   | 1.2   |
| 77.5° | 0.6   |
| 80°   | 0.6   |
| 82.5° | 0.0   |
| 85°   | 0.0   |
| 87.5° | 0.0   |
| 90°   | 0.0   |



Report Generated By 670246072 / DESKTOP-50001EG







— 0°-180°







(END OF REPORT)