

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P859207

Luminaire Tested: **LX4C60D010 EX4C609030 4LBWLI**

Issue Date: 2/8/2022



Test Information

Test Method: LM-79-08
Report Number: P859207
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P208077)
Test Lab: INNOVATION CENTER
Issue Date: 2/8/2022
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LX4C60D010 EX4C609030 4LBWLI
Description: 4 INCH 6000 LUMEN PORTFOLIO LED DOWNLIGHT WITH, 3000K, 90CRI LEDS
AND 4LBW TRIM WITH LI FINISH
Light Source: -
Ballast/Driver:

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 6315.0 lumens
Efficiency: N/A
Efficacy: 87.7 lumens/watt
Spacing Criteria (0/90/45): 1.29 / 1.29 / 1.18
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct

Input Watts (W): 72
Input Voltage (V):
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P859207

CATALOG NUMBER: LX4C60D010 EX4C609030 4LBWLI

Luminous Intensity Polar Plot





TEST NUMBER: P859207

CATALOG NUMBER: LX4C60D010 EX4C609030 4LBWLI

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100	100	100	100
1	113	110	107	105	110	108	105	103	104	102	100	100	98	97	96	95	94	92	92	92	92
2	106	101	97	93	104	99	95	92	96	93	90	93	90	88	90	88	86	84	84	84	84
3	100	93	87	83	98	92	86	82	89	85	81	86	83	80	84	81	78	77	77	77	77
4	94	86	79	75	92	84	79	74	82	77	73	80	76	72	78	75	72	70	70	70	70
5	88	79	72	68	87	78	72	67	76	71	67	74	70	66	73	69	65	64	64	64	64
6	83	73	66	62	82	72	66	61	71	65	61	69	64	60	68	63	60	58	58	58	58
7	78	68	61	56	77	67	61	56	66	60	56	64	59	55	63	59	55	54	54	54	54
8	74	63	56	52	72	62	56	51	61	55	51	60	55	51	59	54	51	49	49	49	49
9	69	59	52	48	68	58	52	47	57	51	47	56	51	47	55	50	47	45	45	45	45
10	66	55	48	44	65	54	48	44	53	48	44	53	47	44	52	47	43	42	42	42	42

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P859207

CATALOG NUMBER: LX4C60D010 EX4C609030 4LBWLI

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	378.4	6.0
10°-20°	1194.1	18.9
20°-30°	1862.8	29.5
30°-40°	1812.5	28.7
40°-50°	905.3	14.3
50°-60°	140.2	2.2
60°-70°	17.0	0.3
70°-80°	4.7	0.1
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	3435.3	54.4
0°-40°	5247.8	83.1
0°-60°	6293.3	99.7
0°-90°	6315.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	6315.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	3869	
5°	3920	378
15°	4216	1194
25°	4094	1863
35°	2944	1813
45°	1136	905
55°	116	140
65°	14	17
75°	7	5
85°	0	0
90°	0	



TEST NUMBER: P859207

CATALOG NUMBER: LX4C60D010 EX4C609030 4LBWLI

CANDELA DISTRIBUTION (FULL):

	0°
0°	3869.2
2.5°	3883.7
5°	3919.9
7.5°	3977.8
10°	4050.2
12.5°	4144.0
15°	4216.4
17.5°	4274.4
20°	4281.6
22.5°	4230.9
25°	4093.6
27.5°	3890.9
30°	3637.8
32.5°	3319.8
35°	2943.6
37.5°	2531.2
40°	2097.3
42.5°	1634.6
45°	1135.6
47.5°	730.4
50°	441.1
52.5°	238.6
55°	115.9
57.5°	50.7
60°	29.0
62.5°	21.7
65°	14.5
67.5°	14.5
70°	7.2
72.5°	7.2
75°	7.2
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-50001EG





— 0°-180°







(END OF REPORT)