

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P859218

Luminaire Tested: **LX4C60D010 EX4C609035 4LBMDH**

Issue Date: 2/18/2022



Test Information

Test Method: LM-79-08
Report Number: P859218
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2105-247-9)
Test Lab: INNOVATION CENTER
Issue Date: 2/18/2022
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LX4C60D010 EX4C609035 4LBMDH
Description: 4 INCH 6000 LUMEN PORTFOLIO LED DOWNLIGHT WITH, 3500K, 90CRI LEDS
AND 4LRMD45 TRIM WITH H FINISH
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 4598.0 lumens
Efficiency: N/A
Efficacy: 63.9 lumens/watt
Spacing Criteria (0/90/45): 0.86 / 0.86 / 0.83
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 72
Input Voltage (V):
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P859218

CATALOG NUMBER: LX4C60D010 EX4C609035 4LBMDH

Luminous Intensity Polar Plot





TEST NUMBER: P859218

CATALOG NUMBER: LX4C60D010 EX4C609035 4LBMDH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

| | | | | | | | | | | | | | | | | | | | | |
|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|----|
| RF | 20 | | | | 20 | | | | 20 | | | | 20 | | | | 20 | | | |
| RC | 80 | | | | 70 | | | | 50 | | | | 30 | | | | 10 | | 0 | |
| RW | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 |
| RCR | | | | | | | | | | | | | | | | | | | | |
| 0 | 119 | 119 | 119 | 119 | 116 | 116 | 116 | 116 | 111 | 111 | 111 | 106 | 106 | 106 | 102 | 102 | 102 | 100 | | |
| 1 | 113 | 111 | 108 | 106 | 111 | 109 | 106 | 104 | 104 | 103 | 101 | 101 | 99 | 98 | 97 | 96 | 95 | 93 | | |
| 2 | 108 | 103 | 99 | 95 | 106 | 101 | 97 | 94 | 98 | 95 | 92 | 95 | 92 | 90 | 92 | 90 | 88 | 87 | | |
| 3 | 102 | 96 | 91 | 87 | 100 | 94 | 90 | 86 | 92 | 88 | 85 | 89 | 86 | 83 | 87 | 84 | 82 | 81 | | |
| 4 | 97 | 90 | 84 | 80 | 95 | 88 | 83 | 79 | 86 | 82 | 78 | 84 | 80 | 77 | 82 | 79 | 77 | 75 | | |
| 5 | 92 | 84 | 78 | 74 | 91 | 83 | 77 | 73 | 81 | 76 | 73 | 79 | 75 | 72 | 78 | 74 | 71 | 70 | | |
| 6 | 88 | 79 | 73 | 68 | 86 | 78 | 72 | 68 | 76 | 71 | 68 | 75 | 71 | 67 | 74 | 70 | 67 | 65 | | |
| 7 | 83 | 74 | 68 | 64 | 82 | 73 | 68 | 64 | 72 | 67 | 63 | 71 | 66 | 63 | 70 | 66 | 63 | 61 | | |
| 8 | 79 | 70 | 64 | 60 | 78 | 69 | 63 | 60 | 68 | 63 | 59 | 67 | 62 | 59 | 66 | 62 | 59 | 57 | | |
| 9 | 76 | 66 | 60 | 56 | 74 | 65 | 60 | 56 | 64 | 59 | 56 | 64 | 59 | 56 | 63 | 58 | 55 | 54 | | |
| 10 | 72 | 62 | 57 | 53 | 71 | 62 | 56 | 53 | 61 | 56 | 53 | 60 | 56 | 52 | 60 | 55 | 52 | 51 | | |

AVERAGE LUMINANCE (cd/sqm):

| | |
|-----|--------|
| | 0° |
| 0° | 680522 |
| 5° | 671332 |
| 10° | 639836 |
| 15° | 592069 |
| 20° | 532979 |
| 25° | 442787 |
| 30° | 321878 |
| 35° | 208647 |
| 40° | 126262 |
| 45° | 65066 |
| 50° | 29472 |
| 55° | 17735 |
| 60° | 11892 |
| 65° | 8517 |
| 70° | 6394 |
| 75° | 4225 |
| 80° | 2688 |
| 85° | 1832 |



TEST NUMBER: P859218

CATALOG NUMBER: LX4C60D010 EX4C609035 4LBMDH

ZONAL LUMENS:

| Zone | Lumens | % Fixture |
|-----------|--------|-----------|
| 0°-10° | 509.6 | 11.1 |
| 10°-20° | 1299.0 | 28.3 |
| 20°-30° | 1468.9 | 31.9 |
| 30°-40° | 887.7 | 19.3 |
| 40°-50° | 310.9 | 6.8 |
| 50°-60° | 79.6 | 1.7 |
| 60°-70° | 30.5 | 0.7 |
| 70°-80° | 10.2 | 0.2 |
| 80°-90° | 1.5 | 0.0 |
| 90°-100° | 0.0 | 0.0 |
| 100°-110° | 0.0 | 0.0 |
| 110°-120° | 0.0 | 0.0 |
| 120°-130° | 0.0 | 0.0 |
| 130°-140° | 0.0 | 0.0 |
| 140°-150° | 0.0 | 0.0 |
| 150°-160° | 0.0 | 0.0 |
| 160°-170° | 0.0 | 0.0 |
| 170°-180° | 0.0 | 0.0 |
| 0°-30° | 3277.5 | 71.3 |
| 0°-40° | 4165.2 | 90.6 |
| 0°-60° | 4555.7 | 99.1 |
| 0°-90° | 4598.0 | 100.0 |
| 90°-120° | 0.0 | 0.0 |
| 90°-150° | 0.0 | 0.0 |
| 90°-180° | 0.0 | 0.0 |
| 0°-180° | 4598.0 | 100.0 |

CANDELA DISTRIBUTION:

| | 0° | Flux |
|-----|------|------|
| 0° | 5539 | |
| 5° | 5444 | 510 |
| 15° | 4655 | 1299 |
| 25° | 3266 | 1469 |
| 35° | 1391 | 888 |
| 45° | 374 | 311 |
| 55° | 83 | 80 |
| 65° | 29 | 30 |
| 75° | 9 | 10 |
| 85° | 1 | 2 |
| 90° | 0 | |



TEST NUMBER: P859218

CATALOG NUMBER: LX4C60D010 EX4C609035 4LBMDH

CANDELA DISTRIBUTION (FULL):

| | 0° |
|-------|--------|
| 0° | 5539.3 |
| 2.5° | 5516.3 |
| 5° | 5443.7 |
| 7.5° | 5315.0 |
| 10° | 5129.0 |
| 12.5° | 4904.8 |
| 15° | 4655.1 |
| 17.5° | 4381.2 |
| 20° | 4076.7 |
| 22.5° | 3703.4 |
| 25° | 3266.5 |
| 27.5° | 2765.8 |
| 30° | 2269.0 |
| 32.5° | 1793.8 |
| 35° | 1391.2 |
| 37.5° | 1054.9 |
| 40° | 787.3 |
| 42.5° | 565.6 |
| 45° | 374.5 |
| 47.5° | 230.6 |
| 50° | 154.2 |
| 52.5° | 110.8 |
| 55° | 82.8 |
| 57.5° | 63.7 |
| 60° | 48.4 |
| 62.5° | 38.2 |
| 65° | 29.3 |
| 67.5° | 22.9 |
| 70° | 17.8 |
| 72.5° | 12.7 |
| 75° | 8.9 |
| 77.5° | 6.4 |
| 80° | 3.8 |
| 82.5° | 2.5 |
| 85° | 1.3 |
| 87.5° | 0.0 |
| 90° | 0.0 |



Report Generated By 670246072 / DESKTOP-50001EG





— 0°-180°







(END OF REPORT)