

Scaled data based on original data using  
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State  
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P#

Luminaire Tested: **LD4C45D010 EX4C459040 4LBSQH**

Issue Date: 2/9/2022



**Test Information**


Test Method: LM-79-08  
Report Number: P#  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P207151)  
Test Lab: INNOVATION CENTER  
Issue Date: 2/9/2022  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: PORTFOLIO  
Catalog Number: LD4C45D010 EX4C459040 4LBSQH  
Description: 4 INCH 4500 LUMEN PORTFOLIO LED DOWNLIGHT WITH, 4000K, 90CRI LEDS  
AND 4LBSQ TRIM WITH H FINISH  
Light Source: -  
Ballast/Driver: -

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 3768.0 lumens  
Efficiency: N/A  
Efficacy: 76.0 lumens/watt  
Spacing Criteria (0/90/45): 0.95 / 0.95 / 0.93  
Luminous Opening: Rectangular (W 0.33' x L: 0.33' x H: 0')  
CIE Type: Direct  
  
Input Watts (W): 49.6  
Input Voltage (V):  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT

TEST NUMBER: P#  
CATALOG NUMBER: LD4C45D010 EX4C459040 4LBSQH

### Luminous Intensity Polar Plot





TEST NUMBER: P#

CATALOG NUMBER: LD4C45D010 EX4C459040 4LBSQH

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100	100	100	100
1	113	110	108	105	111	108	106	104	104	102	100	100	99	97	97	96	95	93	93	93	93
2	107	102	98	94	105	100	96	93	97	94	91	94	91	89	91	89	87	85	85	85	85
3	101	94	89	85	99	93	88	84	90	86	83	88	84	82	86	83	80	79	79	79	79
4	96	88	82	77	94	86	81	77	84	80	76	82	78	75	80	77	74	73	73	73	73
5	90	82	75	71	89	81	75	70	79	74	70	77	73	69	75	72	69	67	67	67	67
6	86	76	70	65	84	75	69	65	74	68	64	72	68	64	71	67	64	62	62	62	62
7	81	71	65	60	80	70	64	60	69	64	60	68	63	59	67	62	59	58	58	58	58
8	77	67	60	56	75	66	60	56	65	59	56	64	59	55	63	58	55	54	54	54	54
9	73	63	56	52	72	62	56	52	61	56	52	60	55	52	59	55	52	50	50	50	50
10	69	59	53	49	68	59	53	49	58	52	49	57	52	48	56	52	48	47	47	47	47

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	360502
5°	355263
10°	340422
15°	321534
20°	300127
25°	272451
30°	227466
35°	164790
40°	103159
45°	58963
50°	30743
55°	17226
60°	10980
65°	6484
70°	4824
75°	2125
80°	3167
85°	0



TEST NUMBER: P#

CATALOG NUMBER: LD4C45D010 EX4C459040 4LBSQH

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	343.8	9.1
10°-20°	901.9	23.9
20°-30°	1159.1	30.8
30°-40°	872.1	23.1
40°-50°	350.2	9.3
50°-60°	99.6	2.6
60°-70°	31.5	0.8
70°-80°	9.0	0.2
80°-90°	0.8	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2404.8	63.8
0°-40°	3276.9	87.0
0°-60°	3726.7	98.9
0°-90°	3768.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	3768.0	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	3736	
5°	3668	344
15°	3219	902
25°	2559	1159
35°	1399	872
45°	432	350
55°	102	100
65°	28	32
75°	6	9
85°	0	1
90°	0	



TEST NUMBER: P#

CATALOG NUMBER: LD4C45D010 EX4C459040 4LBSQH

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	3736.2
2.5°	3713.4
5°	3667.9
7.5°	3582.6
10°	3474.5
12.5°	3343.9
15°	3218.8
17.5°	3076.5
20°	2922.9
22.5°	2758.2
25°	2559.1
27.5°	2320.1
30°	2041.6
32.5°	1728.7
35°	1399.0
37.5°	1091.8
40°	819.0
42.5°	602.8
45°	432.1
47.5°	295.8
50°	204.8
52.5°	142.2
55°	102.4
57.5°	74.0
60°	56.9
62.5°	39.8
65°	28.4
67.5°	22.8
70°	17.1
72.5°	11.4
75°	5.7
77.5°	5.7
80°	5.7
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-50001EG







— 0°-180°







(END OF REPORT)